

Inline ME terminal - IB IL 24 DI 16-ME - 2897156

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Inline, Digital input terminal, Digital inputs: 16, 24 V DC, connection method: 3-wire, transmission speed in the local bus: 500 kbps, degree of protection: IP20, including Inline connectors and marking fields

Product Description

The terminal is designed for use within an Inline station. It is used to acquire digital signals.

Why buy this product

- 16 digital inputs
- Connection of sensors in 2 and 3-wire technology
- Maximum permissible load current per sensor: 250 mA
- Diagnostic and status indicators



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 STK |
| Minimum order quantity | 4 STK |
| GTIN |  4 046356 148207 |
| GTIN | 4046356148207 |
| Weight per Piece (excluding packing) | 193.450 g |
| Custom tariff number | 85389091 |
| Country of origin | Germany |

Technical data

Note

| | |
|-------------------------|---|
| Utilization restriction | EMC: class A product, see manufacturer's declaration in the download area |
|-------------------------|---|

Inline ME terminal - IB IL 24 DI 16-ME - 2897156

Technical data

Dimensions

| | |
|--------------------|--------------------|
| Width | 48.8 mm |
| Height | 119.8 mm |
| Depth | 71.5 mm |
| Note on dimensions | Housing dimensions |

Ambient conditions

| | |
|--|---|
| Ambient temperature (operation) | -25 °C ... 55 °C |
| Ambient temperature (storage/transport) | -25 °C ... 85 °C |
| Permissible humidity (operation) | 10 % ... 95 % (according to DIN EN 61131-2) |
| Permissible humidity (storage/transport) | 10 % ... 95 % (according to DIN EN 61131-2) |
| Air pressure (operation) | 70 kPa ... 106 kPa (up to 3000 m above sea level) |
| Air pressure (storage/transport) | 70 kPa ... 106 kPa (up to 3000 m above sea level) |
| Degree of protection | IP20 |

General

| | |
|-------------------------------|--------------|
| Mounting type | DIN rail |
| Net weight | 122 g |
| Note on weight specifications | without plug |

Interfaces

| | |
|--------------------|----------------------------------|
| Designation | Inline local bus |
| No. of channels | 2 |
| Connection method | Inline data jumper |
| Transmission speed | 500 kbps (automatic recognition) |

Inline potentials

| | |
|----------------------|--|
| Designation | Communications power (U_L) |
| Supply voltage | 7.5 V DC |
| Current consumption | max. 60 mA |
| Designation | Segment circuit supply (U_S) |
| Supply voltage | 24 V DC (via voltage jumper) |
| Supply voltage range | 19.2 V DC ... 30 V DC (including all tolerances, including ripple) |
| Current consumption | max. 4 A |

Digital inputs

| | |
|--------------------------|------------------------|
| Input name | Digital inputs |
| Description of the input | IEC 61131-2 type 1 |
| Connection method | Spring-cage connection |
| Connection technology | 3-wire |
| Number of inputs | 16 |

Inline ME terminal - IB IL 24 DI 16-ME - 2897156

Technical data

Digital inputs

| | |
|--------------------------------|---------------------------------------|
| Typical response time | < 1 ms |
| Type of protection | Short-circuit and overload protection |
| Input voltage | 24 V DC |
| Input voltage range "0" signal | -3 V DC ... 5 V |
| Input voltage range "1" signal | 15 V DC ... 30 V DC |

Electrical isolation

| | |
|--------------|---|
| Test section | 5 V supply, incoming remote bus/7.5 V supply (bus logics) 500 V AC 50 Hz 1 min. |
| | 5 V supply, outgoing remote bus/7.5 V supply (bus logics) 500 V AC 50 Hz 1 min. |
| | 7.5 V supply (bus logics)/24 V supply (I/O) 500 V AC 50 Hz 1 min. |
| | 24 V supply (I/O) / functional earth ground 500 V AC 50 Hz 1 min. |

Standards and Regulations

| | |
|------------------|--------------------------------------|
| Protection class | III, IEC 61140, EN 61140, VDE 0140-1 |
|------------------|--------------------------------------|

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27250302 |
| eCl@ss 4.1 | 27250302 |
| eCl@ss 5.0 | 27250302 |
| eCl@ss 5.1 | 27242604 |
| eCl@ss 6.0 | 27242604 |
| eCl@ss 7.0 | 27242604 |
| eCl@ss 8.0 | 27242604 |
| eCl@ss 9.0 | 27242604 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC001430 |
| ETIM 3.0 | EC001599 |
| ETIM 4.0 | EC001599 |
| ETIM 5.0 | EC001599 |
| ETIM 6.0 | EC001599 |

Inline ME terminal - IB IL 24 DI 16-ME - 2897156

Classifications

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 43172015 |
| UNSPSC 7.0901 | 43201404 |
| UNSPSC 11 | 43172015 |
| UNSPSC 12.01 | 43201404 |
| UNSPSC 13.2 | 32151602 |

Approvals

Approvals

Approvals

EAC / UL Recognized / cUL Recognized / cULus Recognized

Ex Approvals

Approval details

| | | |
|-----|--|---------------|
| EAC | | EAC-Zulassung |
|-----|--|---------------|

| | | | |
|---------------|--|---|---------------|
| UL Recognized | | http://database.ul.com/cgi-bin/XYVV/template/LISEXT/1FRAME/index.htm | FILE E 140324 |
|---------------|--|---|---------------|

| | | | |
|----------------|--|---|---------------|
| cUL Recognized | | http://database.ul.com/cgi-bin/XYVV/template/LISEXT/1FRAME/index.htm | FILE E 140324 |
|----------------|--|---|---------------|

| | | |
|------------------|--|---|
| cULus Recognized | | http://database.ul.com/cgi-bin/XYVV/template/LISEXT/1FRAME/index.htm |
|------------------|--|---|

Accessories

Accessories

Front adapter

Inline ME terminal - IB IL 24 DI 16-ME - 2897156

Accessories

Front adapters - FLKM 14-PA-INLINE/IN16 - 2302751



VARIOFACE front adapter for Inline modules, for transferring 16 (2 x 8) digital input signals.

Labeling panel

Labeling field - IB IL FIELD 2 - 2727501

Labeling field, width: 12.2 mm



Labeling field - IB IL FIELD 8 - 2727515

Labeling field, width: 48.8 mm



Terminal marking

Insert strip - ESL 62X10 - 0809492

Insert strip, Sheet, white, unlabeled, can be labeled with: Office printing systems: Laser printer, mounting type: insert, lettering field size: 62 x 10 mm



Insert strip - ESL 62X46 - 0809502

Insert strip, Sheet, white, unlabeled, can be labeled with: Office printing systems: Laser printer, mounting type: insert, lettering field size: 62 x 46 mm



Inline ME terminal - IB IL 24 DI 16-ME - 2897156

Accessories

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>