

Interface module - VIP-3/SC/D37SUB/M/HW/C300 - 2900675

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



VARIOFACE module, with screw connection and male D-Subminiature pin strip, for mounting on NS 35 rails, 37-pos.



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	200.0 g
Custom tariff number	85369010
Country of origin	United States

Technical data

Dimensions

Width	88 mm
Height	69 mm
Depth	62 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

General

Max. perm. operating voltage	24 V DC
Max. perm. current (per branch)	2 A
Number of positions	37
Status display	No
Mounting position	any
Assembly instructions	In rows with zero spacing
Standards/regulations	DIN EN 50178

Interface module - VIP-3/SC/D37SUB/M/HW/C300 - 2900675

Technical data

Connection data for connection 1

Connection name	Field level
Connection in acc. with standard	IEC / EN
Connection method	Screw connection
Stripping length	8 mm
Screw thread	M 3
Conductor cross section solid	0.2 mm ² ... 4 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12

Connection data for connection 2

Connection name	Controller level
Connection method	D-SUB pin strip
Number of connections	1
Number of positions	37

Supported controller

Controller	HONEYWELL Experion PKS C300/C-Series
- suitable I/O card	TAIX01 (non-redundant)
	TAIX11 (redundant)

Standards and Regulations

Connection in acc. with standard	CUL
Standards/regulations	DIN EN 50178

Classifications

eCl@ss

eCl@ss 4.0	27250313
eCl@ss 4.1	27250313
eCl@ss 5.0	27250313
eCl@ss 5.1	27250313
eCl@ss 6.0	27242608
eCl@ss 7.0	27141152
eCl@ss 8.0	27141152

ETIM

ETIM 2.0	EC001434
ETIM 3.0	EC001604
ETIM 4.0	EC001604

Interface module - VIP-3/SC/D37SUB/M/HW/C300 - 2900675

Classifications

ETIM

ETIM 5.0	EC002780
----------	----------

UNSPSC

UNSPSC 6.01	30211824
UNSPSC 7.0901	39121421
UNSPSC 11	39121421
UNSPSC 12.01	39121421
UNSPSC 13.2	39121421

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / EAC / CSA / EAC / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

UL Recognized	
mm ² /AWG/kcmil	30-12
Nominal current IN	2 A
Nominal voltage UN	125 V

cUL Recognized	
mm ² /AWG/kcmil	30-12
Nominal current IN	2 A

Interface module - VIP-3/SC/D37SUB/M/HW/C300 - 2900675

Approvals

Nominal voltage UN	125 V
--------------------	-------

EAC


CSA	
mm ² /AWG/kcmil	28-14
Nominal current IN	2 A
Nominal voltage UN	105 V

EAC

cULus Recognized

Drawings

Circuit diagram



Connection scheme VIP-3/SC/D37SUB/M/HW/C300