

PV string monitoring module - SCK-C-MODBUS - 2901674

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



SCK communication module for acquiring up to 8 x SCK measuring modules, RS-485 Modbus/RTU output

Product Features

- Digital input for monitoring the remote indication contacts of surge protection modules
- Internal temperature monitoring of measuring module
- Measuring modules supplied via the communication module



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	162.0 g
Custom tariff number	85176200
Country of origin	Germany

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	22.5 mm
Height	102 mm
Depth	106 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Maximum altitude	≤ 2000 m

PV string monitoring module - SCK-C-MODBUS - 2901674

Technical data

Ambient conditions

Degree of protection	IP20
----------------------	------

Switching output

Output name	No switching output
-------------	---------------------

Power supply

Nominal supply voltage	24 V DC -10 % ... +25 %
Max. current consumption	800 mA
Own current consumption	22 mA (typical)
	45 mA (maximum)
Power consumption	580 mW (24 V DC)

Connection data

Connection method	Screw connection
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	2.5 mm ²
Conductor cross section AWG min.	24
Conductor cross section AWG max.	12
Conductor cross section flexible min.	0.2 mm ²
Conductor cross section flexible max.	2.5 mm ²

General

Degree of pollution	2
Standards/regulations	EN 61010-1
Electromagnetic compatibility	Conformance with EMC directive 2004/108/EC and for low-voltage directive 2006/95/EC
Noise emission	EN 61000-6-4
Noise immunity	EN 61000-6-2 When being exposed to interference, there may be minimal deviations.
Mounting position	any
Assembly instructions	Horizontal or vertical
Conformance	CE-compliant
UL, USA	1741 Recognized
UL, USA / Canada	508 Listed
Torque	0.5 Nm ... 0.6 Nm

Standards and Regulations

Electromagnetic compatibility	Conformance with EMC directive 2004/108/EC and for low-voltage directive 2006/95/EC
Noise emission	EN 61000-6-4
Connection in acc. with standard	UL

PV string monitoring module - SCK-C-MODBUS - 2901674

Technical data

Standards and Regulations

Standards/regulations	EN 61010-1
Conformance	CE-compliant
UL, USA	1741 Recognized
UL, USA / Canada	508 Listed

Classifications

eCl@ss

eCl@ss 4.0	27210902
eCl@ss 4.1	27371105
eCl@ss 5.0	27371801
eCl@ss 5.1	27210902
eCl@ss 6.0	27210902
eCl@ss 7.0	27210902
eCl@ss 8.0	27210123
eCl@ss 9.0	27210123

ETIM

ETIM 3.0	EC001505
ETIM 4.0	EC001423
ETIM 5.0	EC002475

UNSPSC

UNSPSC 6.01	30211506
UNSPSC 7.0901	39121008
UNSPSC 11	39121008
UNSPSC 12.01	39121008
UNSPSC 13.2	39121008

Approvals

Approvals

Approvals

UL Recognized / UL Listed / cUL Listed / cULus Listed

Ex Approvals

PV string monitoring module - SCK-C-MODBUS - 2901674

Approvals

Approvals submitted

Approval details

UL Recognized

UL Listed

cUL Listed

cULus Listed

Drawings

Block diagram

