

Test plugs - PS-UK 2,5 B/Z-6 - 3001239

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Test plugs, color: red

Your advantages

- ✓ The test plug reliably makes contact in the bridge shaft and in all test sockets with a 2.3 mm or 4 mm diameter
- ✓ Individual test adapters can be combined using the modular PS-...2,3MM test plug.

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 089856
GTIN	4017918089856
Weight per Piece (excluding packing)	55.000 g
Custom tariff number	85366990
Country of origin	Poland

Technical data

Dimensions

Length	19.6 mm
Width	5 mm
Pitch	6.2 mm
Pin diameter	6.5 mm

General

Color	red
Material	PA

Test plugs - PS-UK 2,5 B/Z-6 - 3001239

Technical data

Ambient temperature (operation)	-40 °C ... 115 °C
---------------------------------	-------------------

Standards and Regulations

Flammability rating according to UL 94	V2
--	----

Environmental Product Compliance

	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss

eCl@ss 4.1	27141100
eCl@ss 5.1	27141100
eCl@ss 6.0	27141100
eCl@ss 7.0	27440313
eCl@ss 8.0	27440313
eCl@ss 9.0	27440313

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC002255
ETIM 5.0	EC002255
ETIM 6.0	EC002255
ETIM 7.0	EC002255

UNSPSC

UNSPSC 6.01	30211812
UNSPSC 7.0901	39121410
UNSPSC 11	39121411
UNSPSC 12.01	39121411
UNSPSC 13.2	39121410

Approvals

Approvals

Test plugs - PS-UK 2,5 B/Z-6 - 3001239

Approvals

Approvals

EAC / EAC

Ex Approvals

Approval details

EAC		EAC-Zulassung
EAC		RU C- DE.A*30.B.01742