

Strain relief - PDZ/4 - 3040575

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Strain relief, length: 28.9 mm, width: 19.8 mm, number of positions: 4, color: black




Your advantages

- The conductor can be fixed using Phoenix Contact cable binders
- The strain relief is snapped into the plug center on the spring-cage plugs or spring-cage couplings



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	50 pc
GTIN	 4 017918 832711
GTIN	4017918832711
Weight per Piece (excluding packing)	0.810 g
Custom tariff number	39269097
Country of origin	Poland

Technical data

General

Number of positions	4
Color	black
Material	PA-GF
Flammability rating according to UL 94	V0

Dimensions

Width	19.8 mm
-------	---------

Strain relief - PDZ/4 - 3040575

Technical data

Dimensions

Length	28.9 mm
--------	---------

Standards and Regulations

Flammability rating according to UL 94	V0
----------------------------------------	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 10.0.1	27141190
eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141145
eCl@ss 5.1	27141100
eCl@ss 6.0	27141100
eCl@ss 7.0	27141190
eCl@ss 8.0	27141190
eCl@ss 9.0	27141190

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC002498
ETIM 5.0	EC002848
ETIM 6.0	EC002848
ETIM 7.0	EC002848

UNSPSC

UNSPSC 6.01	30211812
UNSPSC 7.0901	39121411
UNSPSC 11	39121411
UNSPSC 12.01	39121411
UNSPSC 13.2	39121410