

## Feed-through terminal block - UT 4-MTD BK - 3047691

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Feed-through terminal block, Connection method: Screw connection, Number of positions: 1, Cross section: 0.14 mm<sup>2</sup> - 6 mm<sup>2</sup>, AWG: 26 - 10, Width: 6.2 mm, Color: black, Mounting type: NS 35/7,5, NS 35/15



### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Minimum order quantity               | 50 pc    |
| Weight per Piece (excluding packing) | 11.2 g   |
| Custom tariff number                 | 85369010 |
| Country of origin                    | Germany  |

### Technical data

#### General

|  |   |
|--|---|
| Number of levels                       | 1   |
| Number of connections                  | 2   |
| Nominal cross section                  | 4 mm <sup>2</sup>                                     |
| Color                                  | black   |
| Insulating material                    | PA  |
| Flammability rating according to UL 94 | V0  |
| Rated surge voltage                    | 8 kV  |
| Degree of pollution                    | 3   |
| Overvoltage category                   | III   |
| Insulating material group              | I   |
| Maximum load current                   | 41 A (with 6 mm <sup>2</sup> conductor cross section) |
| Nominal current I <sub>N</sub>         | 41 A  |
| Nominal voltage U <sub>N</sub>         | 800 V   |

# Feed-through terminal block - UT 4-MTD BK - 3047691

## Technical data

### General

|                 |     |
|-----------------|-----|
| Open side panel | Yes |
|-----------------|-----|

### Dimensions

|                  |         |
|------------------|---------|
| Width            | 6.2 mm  |
| End cover width  | 2.2 mm  |
| Length           | 57.8 mm |
| Height NS 35/7,5 | 47.5 mm |
| Height NS 35/15  | 55 mm   |

### Connection data

|   |                      |
|---|----------------------|
| Connection method   | Screw connection     |
| Connection in acc. with standard  | IEC 60947-7-1        |
| Conductor cross section solid min.  | 0.14 mm <sup>2</sup> |
| Conductor cross section solid max.  | 6 mm <sup>2</sup>    |
| Conductor cross section AWG min.  | 26                   |
| Conductor cross section AWG max.  | 10                   |
| Conductor cross section flexible min.   | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible max.   | 6 mm <sup>2</sup>    |
| Min. AWG conductor cross section, flexible  | 26                   |
| Max. AWG conductor cross section, flexible  | 10                   |
| Conductor cross section flexible, with ferrule without plastic sleeve min.              | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule without plastic sleeve max.              | 4 mm <sup>2</sup>    |
| Conductor cross section flexible, with ferrule with plastic sleeve min.                 | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule with plastic sleeve max.                 | 4 mm <sup>2</sup>    |
| 2 conductors with same cross section, solid min.  | 0.14 mm <sup>2</sup> |
| 2 conductors with same cross section, solid max.  | 1.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded min.                                     | 0.14 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded max.                                     | 1.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. | 0.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 2.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, min.   | 0.14 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, max.   | 1.5 mm <sup>2</sup>  |
| Connection in acc. with standard  | IEC/EN 60079-7       |
| Conductor cross section solid min.  | 0.14 mm <sup>2</sup> |
| Conductor cross section solid max.  | 6 mm <sup>2</sup>    |
| Conductor cross section AWG min.  | 26                   |

# Feed-through terminal block - UT 4-MTD BK - 3047691

## Technical data

### Connection data

|                                       |                      |
|---------------------------------------|----------------------|
| Conductor cross section AWG max.      | 10                   |
| Conductor cross section flexible min. | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible max. | 4 mm <sup>2</sup>    |
| Stripping length                      | 9 mm                 |
| Internal cylindrical gage             | A4                   |
| Screw thread                          | M3                   |
| Tightening torque, min                | 0.6 Nm               |
| Tightening torque max                 | 0.8 Nm               |

### Standards and Regulations

|  |               |
|--|---------------|
| Connection in acc. with standard       | CSA           |
|  | IEC 60947-7-1 |
| Flammability rating according to UL 94 | V0            |

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141120 |
| eCl@ss 4.1 | 27141120 |
| eCl@ss 5.0 | 27141120 |
| eCl@ss 5.1 | 27141120 |
| eCl@ss 6.0 | 27141120 |
| eCl@ss 7.0 | 27141120 |
| eCl@ss 8.0 | 27141120 |
| eCl@ss 9.0 | 27141120 |

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000897 |
| ETIM 3.0 | EC000897 |
| ETIM 4.0 | EC000897 |
| ETIM 5.0 | EC000897 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121410 |

# Feed-through terminal block - UT 4-MTD BK - 3047691

## Approvals

### Approvals

#### Approvals


CSA / UL Recognized / cUL Recognized / DNV / VDE Gutachten mit Fertigungsüberwachung / IECEx CB Scheme / EAC / cULus Recognized


#### Ex Approvals


IECEx / ATEX / UL Recognized / cUL Recognized / EAC Ex

#### Approvals submitted

## Approval details

|  |       |       |
|--|-------|-------|
| CSA  |       |       |
|  | B     | C     |
| mm <sup>2</sup> /AWG/kcmil   | 26-10 | 26-10 |
| Nominal current I <sub>N</sub>   | 30 A  | 30 A  |
| Nominal voltage U <sub>N</sub>   | 600 V | 600 V |

|   |       |       |
|---|-------|-------|
| UL Recognized  |       |       |
|   | B     | C     |
| mm <sup>2</sup> /AWG/kcmil  | 26-10 | 26-10 |
| Nominal current I <sub>N</sub>  | 30 A  | 30 A  |
| Nominal voltage U <sub>N</sub>  | 600 V | 600 V |

|  |       |       |
|--|-------|-------|
| cUL Recognized  |       |       |
|  | B     | C     |
| mm <sup>2</sup> /AWG/kcmil   | 26-10 | 26-10 |
| Nominal current I <sub>N</sub>   | 30 A  | 30 A  |
| Nominal voltage U <sub>N</sub>   | 600 V | 600 V |


# Feed-through terminal block - UT 4-MTD BK - 3047691

## Approvals

DNV


VDE Gutachten mit Fertigungsüberwachung 

|                            |       |
|----------------------------|-------|
| mm <sup>2</sup> /AWG/kcmil | 0.2-4 |
| Nominal voltage UN         | 800 V |

IECEE CB Scheme 

|                            |       |
|----------------------------|-------|
| mm <sup>2</sup> /AWG/kcmil | 0.2-4 |
| Nominal voltage UN         | 800 V |

EAC

cULus Recognized 

## Drawings

Circuit diagram

