

## Connector - C-SCF 2,5/4,8X0,5 - 3240157

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Slip-on sleeve, non-insulated, 1.5 - 2.5 mm<sup>2</sup>, 4.8 x 0.5

The figure shows a version of the article

### Why buy this product

- The uninsulated slip-on sleeves and flat plugs are made from electrolytically tin-plated brass
- They round out the product range in terms of connectors

### Key Commercial Data

Packing unit	1 STK
Minimum order quantity	100 STK
GTIN	 4 046356 453745
GTIN	4046356453745
Weight per Piece (excluding packing)	0.470 g
Custom tariff number	85369010
Country of origin	Belgium

### Technical data

#### Dimensions

Length (b)	15.6 mm
Width (a)	4.8 mm
Maximum stripping length	8 mm
Material thickness (g)	0.4 mm

#### Ambient conditions

## Connector - C-SCF 2,5/4,8X0,5 - 3240157

### Technical data

#### Ambient conditions

Ambient temperature (operation)	110 °C
---------------------------------	--------

#### General

Color	silver
Stripping length	8 mm
Components	Halogen-free
Material	Brass
Insulating material	nicht zutreffend
Coating	Tin-plated

### Drawings

Dimensional drawing

