

Flat gasket - WP-FS IP68 PG16 - 3241169

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Flat gasket, Height: 2 mm, Diameter: 27 mm, Color: black



Product Features

- The Perbunan flat sealing rings are used to seal protective hose screw connections on uneven surfaces.
- Up to IP68 protection is achieved.

Key Commercial Data

| | |
|------------------------|----------|
| Packing unit | 1 pc |
| Minimum order quantity | 50 pc |
| Custom tariff number | 40169300 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|--------------------|-------|
| Height | 2 mm |
| Diameter | 27 mm |
| Inner diameter (f) | 21 mm |

Ambient conditions

| | |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -20 °C ... 120 °C |
| Degree of protection | IP68 |

General

| | |
|------------|--------------------------------|
| Color | black |
| Components | free from silicone and halogen |
| Material | Perbunan |

Flat gasket - WP-FS IP68 PG16 - 3241169

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27141209 |
| eCl@ss 4.1 | 27141209 |
| eCl@ss 5.0 | 21132007 |
| eCl@ss 5.1 | 27141120 |
| eCl@ss 6.0 | 21132007 |
| eCl@ss 7.0 | 27439210 |
| eCl@ss 8.0 | 27439218 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC000519 |
| ETIM 4.0 | EC000519 |
| ETIM 5.0 | EC001181 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211812 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11 | 39121411 |
| UNSPSC 12.01 | 39121411 |
| UNSPSC 13.2 | 39121411 |