

Termination board - IBS PCI SC/I-T - 2725260

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



PCI master controller board with electrical isolation

Product Description

INTERBUS generation 4 controller board for PCs

With the IBS PCI SC/I-T standard controller, the high-level language programmable ISA bus platform is also extended towards PCI compatibility. The corresponding CMD INTERBUS configurator acts as the central interface to all other tools involved in an automation solution, such as EPLAN, visualization, and programming.

Interfaces that are consistent throughout the system, such as HLI and OPC, offer direct access to the INTERBUS fieldbus system as well as to the runtime system of the controller. Free drivers for Windows NT, XP, and Windows 7 round off the products.

The drivers are not supplied with the board. The necessary software is on the CD and in the user manual, or can be downloaded from this page.

The system packages offered include an inexpensive version consisting of the controller board, user manuals, all drivers (including HLI, but excluding OPC server), and CMD G4.

Why buy this product

- External 24 V DC power supply
- Direct integration into OPC-based visualization systems via OPC server
- Installation of several cards in a PC with monitoring of multiple INTERBUS lines
- Parameterization and diagnostics with Diag+
- Compatible driver
- Access to INTERBUS system data and controller data via visualization stations
- INTERBUS parameter channel (PCP) supported
- Access to high-level language applications via HFI



Key Commercial Data

Packing unit	1 STK
GTIN	 4 017918 185121

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Termination board - IBS PCI SC/I-T - 2725260

Technical data

Dimensions

Width	168 mm
Height	107 mm
Depth	20 mm

Ambient conditions

Degree of protection	IP00
Ambient temperature (operation)	0 °C ... 55 °C (acc. to EN 60204-1)
Ambient temperature (storage/transport)	-25 °C ... 75 °C (acc. to EN 60204-1)
Permissible humidity (operation)	75 % (on average, 85% infrequently, non-condensing)
Air pressure (operation)	860 hPa ... 1080 hPa (up to 2000 m above mean sea level)
Air pressure (storage/transport)	660 hPa ... 1080 hPa (up to 3000 m above sea level)

Control system

Control system	IBM-compatible PCs with PCI slot
Diagnostics tool	DIAG+ from version 1.0x
Configuration tool	CMD from version 4.5x
Operating system	Windows NT
	Windows 2000
	Windows XP
	Windows 7
	Venturcom RTX 5.x
	Further types on request

Software interfaces

Driver	Windows NT
	Windows 2000
	Windows XP
	Windows 7
	Venturcom RTX 5.x
	Further types on request
Application interface	HFI
	OPC
	DDI

Software requirements

Configuration tool	CMD from version 4.5x
	Config+ from version 1.00 onwards
Diagnostics tool	DIAG+ from version 1.0x

Power supply

Power supply connection	Via PCI bus
Typical current consumption	0.7 A
Supply voltage	5 V DC

Termination board - IBS PCI SC/I-T - 2725260

Technical data

Power supply

Supply voltage range	± 5 % (including ripple)
Power dissipation	max. 3.5 W

General

Weight	126.1 g
Format	Short plug-in card, 1-slot

Data interfaces

Interface	INTERBUS remote bus
Connection method	9-pos. D-SUB female connector, with electrical isolation
Interface	Parameterization/operation/diagnostics
Connection method	RS-232-C, Mini-DIN female
Interface	Host system
Connection method	PCI bus, 32 bit, 33 MHz, 5 V
Interface	Direct I/Os
Connection method	14-pos. FLK pin strip
Interrupts	1 IRQ, PnP

Direct I/Os

Input name	Digital inputs
Number of inputs	6 (EN 61131-2 type 1)
Nominal input voltage U_{IN}	24 V DC
Output name	Digital outputs
Number of outputs	2
Connection method	FLK cable connector (14-pos.)
Maximum output current per channel	0.5 A

Fieldbus function

Amount of process data	max. 8192 Bit (INTERBUS-Master)
Number of supported devices	max. 512 (of which 254 are remote bus devices/bus segments)
Number of devices with parameter channel	max. 126

Standards and Regulations

Connection in acc. with standard	CUL
----------------------------------	-----

Classifications

eCl@ss

eCl@ss 4.0	27240603
eCl@ss 4.1	27240603
eCl@ss 5.0	27242208
eCl@ss 5.1	27242208
eCl@ss 6.0	27242208

Termination board - IBS PCI SC/I-T - 2725260

Classifications

eCl@ss

eCl@ss 7.0	27242208
eCl@ss 8.0	27242208

ETIM

ETIM 2.0	EC001425
ETIM 3.0	EC001425
ETIM 4.0	EC000236
ETIM 5.0	EC002631

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / EAC / cULus Recognized

Ex Approvals

Approvals submitted

Approval details


UL Recognized

cUL Recognized

EAC

Termination board - IBS PCI SC/I-T - 2725260

Approvals

cULus Recognized  us

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>