

# Antenna cable - RAD-PIG-EF316-N-N - 2867704

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Adapter cable, 50 cm pigtail, N (male) -> N (female), 50 Ω impedance



## Why buy this product

- As an adapter between devices and cables

## Key Commercial Data

Packing unit	1 STK
GTIN	 4 017918 939076

## Technical data

### Dimensions

Fixed cable length	50 cm
External diameter	2.50 mm

### Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C

### General

Connection 1	Connector connection
Connection method	N (female)
Connection 2	Connector connection
Connection method	N (male)
Cable type	EF 316
Outer sheath, material	RADOX®(LSFH)
Minimum bending radius	12.50 mm
Frequency range	900 MHz
	2.4 GHz
	5 GHz
Impedance	50 Ω

### Attenuation

# Antenna cable - RAD-PIG-EF316-N-N - 2867704

## Technical data

### Attenuation

868 / 900 MHz	0.6 dB
2.4 GHz	1 dB
5 GHz	1.4 dB

## Classifications

### eCl@ss

eCl@ss 4.0	27060805
eCl@ss 4.1	27060805
eCl@ss 5.0	27061805
eCl@ss 5.1	27061805
eCl@ss 6.0	27061805
eCl@ss 7.0	27061805
eCl@ss 8.0	27060310

### ETIM

ETIM 2.0	EC000019
ETIM 3.0	EC000019
ETIM 4.0	EC000019
ETIM 5.0	EC001682

### UNSPSC

UNSPSC 6.01	26121608
UNSPSC 7.0901	26121608
UNSPSC 11	26121608
UNSPSC 12.01	26121608
UNSPSC 13.2	26121608

## Approvals

### Approvals

---

Approvals

EAC / EAC

---

Ex Approvals

---

Approvals submitted

---

## Antenna cable - RAD-PIG-EF316-N-N - 2867704

### Approvals

#### Approval details

EAC

EAC

Phoenix Contact 2016 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>