



Extract from the online catalog

PLC-BSP-120UC/21

Order No.: 2967167



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2967167>

6.2 mm PLC basic terminal blocks with spring-cage connection method, input voltage 120 V AC/DC (without relay or optocoupler)

Commercial data	
EAN	4017918165307
sales group	G201
Pack	10 pcs.
Customs tariff	85364900
Weight/Piece	0.02747 KG

Product notes

WEEE/RoHS-compliant since:
04/18/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Input data	
Nominal input voltage U_N	120 V AC/DC
Status display	LED
Protective circuitry	Bridge rectifier

PLC-BSP-120UC/21 Order No.: 2967167
http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2967167

Output data

Compatible components	Miniature relay, REL-MR-60DC/21AU, REL-MR-60DC/21; miniature optocoupler, OPT-60DC/48DC/100, OPT-60DC/24DC/2, OPT-60DC/230AC/1
-----------------------	--

Connection data

Conductor cross section solid min.	0.14 mm ²
Conductor cross section solid max.	2.5 mm ²
Conductor cross section stranded min.	0.14 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	26
Conductor cross section AWG/kcmil max	14
Type of connection	Spring-cage connection
Stripping length	8 mm

General data

Width	6.2 mm
Height	94 mm
Depth	80 mm
Color	green
Ambient temperature (operation)	-25 °C ... 55 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Operating mode	100% operating factor
Inflammability class acc. to UL 94	V0
Mounting position	Any
Assembly instructions	In rows with zero spacing

Certificates / Approvals



Certification

CUL, CUL Listed, GL, GOST, UL, UL Listed

PLC-BSP-120UC/21 Order No.: 2967167
<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2967167>

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;

onlinecomponents.com