


THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

|                                                |                                                                                                                                                |
|------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| Material                                       | High Conductivity Seamless Copper Tube                                                                                                         |
| Plating                                        | Electro-Tin                                                                                                                                    |
| Wire Size                                      | 1/0 STR/FLEX                                                                                                                                   |
| Wire Type                                      | Stranded Copper: Class B & C, Compact, Class G, H, I, K, M, Locomotive                                                                         |
| Wire Strip Length                              | 3/4 in.                                                                                                                                        |
| Stud Size                                      | 5/16 in.                                                                                                                                       |
| UL Listed Wire Connector                       | Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts. |
| UL Temperature Rating                          | 90° C                                                                                                                                          |
| C.S.A Certified Wire Connector                 | Yes                                                                                                                                            |
| Panduit Color Code on Barrel                   | PINK                                                                                                                                           |
| Panduit Die Index No. on Barrel                | P42                                                                                                                                            |
| Alternate Industry Die Index No. ( ) on Barrel | (12)                                                                                                                                           |



CERTIFIED

LISTED  
Wire Connector



|     |      |     |     |             |       |
|-----|------|-----|-----|-------------|-------|
| 00  | 6/03 | SAC | SAC | RELEASED    | 10850 |
| REV | DATE | BY  | CHK | DESCRIPTION | ECN   |

|                                                              |                                           |
|--------------------------------------------------------------|-------------------------------------------|
| <b>PANDUIT CORP. TINLEY PARK, ILLINOIS</b>                   |                                           |
| LCDX1/0-56D-X<br>Copper Lug - Two-Hole, Standard Flex Barrel |                                           |
| SCALE<br>N/A                                                 | DRAWING NO / CAD FILE<br>LCDX1_0-56D-CUST |