



THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



1.44" [37] CT-2525CH, CT-2550CH & CT-2500CH (WITH LOCATOR)
 1.25" [32] CT-2570CH (WITHOUT LOCATOR)



NOTES, UNLESS OTHERWISE SPECIFIED:

These crimping heads are used with Panduit CT-2500 and CT-2500/E Battery Operated Crimping Tools.

Weight 1.74 lbs. (0,79 kg)
 Dimensions: 5-1/16" L x 2-3/4" H x 1-7/16" W (with Locator)
 [129 L x 70 H x 37 W] mm

CT-2525CH or CD-525 Crimping head or die insert for installing the following Panduit products:
 #26 – #22 AWG insulated terminals and splices,
 #22 – #10 AWG fully insulated disconnects, insulated parallel splices; and
 specific #22 – #14 AWG barrel insulated disconnects.

CT-2550CH or CD-550 Crimping head or die insert for installing the following Panduit products:
 #22 – #10 AWG insulated terminals and splices;
 and specific insulated disconnects.
 Reduced crimp effort advantage for #12 – #10 AWG terminations.

CT-2570CH or CD-570 Crimping head or die insert for installing most of the following Panduit products:
 #22 – #10 AWG and 0,5 – 6,0 mm² non-insulated terminals, disconnects;
 and specific non-insulated splices.

CT-2500CH Crimping head (frame only); to be used with crimping die inserts CD-525, CD-550 or CD-570 (sold separately).

The Crimping Head and/or Die Insert Installation Instructions can be found at www.panduit.com, search for CT-2525CH, CT-2550CH, CT-2570CH, CT-2500CH, CD-525, CD-550 or CD-570.

Dimensions in [brackets] are in millimeters.
 All dimensions are for reference only.

F:\wrkgrp\rvusers\ENGR DOCS\CUSTOMER DRAWINGS\TP25387B01_02 CT-25XXCH CD.doc

**CT-2525CH
 SHOWN ABOVE**

							PANDUIT CORP. TINLEY PARK, ILLINOIS			
							CD*CT-2525CH, CT-2550CH, CT-2570CH, CT-2500CH			
							UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: (.x) ± --- (.xxx) ± --- (.xx) ± --- ANGLES ± ---	UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION.		
02	1-28-14	BLR	<i>SRRE</i>	UPD BRANDING	4704	---	<i>SRRE</i>	DRAWN BY: BLR	MATL: -----	SCALE NONE
01	4-04-08	BLR	BJPU	ADD CT-2500CH & DIE INSERTS	4290	---	JRWA			
00	3-02-07	BLR	SRRE	RELEASED	4241	---	SZ	DATE: 3-02-07	DRAWING NO. TP25387B01	DWG B SIZE
REV	DATE	BY	CHK'D	DESCRIPTION	ECN	- R	CUST	SUP		