

Search Results

- Evaluate
 - FAQ's
- Design a Solution
 - Part Drawings
 - PDFButt Splices..
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips

 Text Search: 'BSV18X-XY'

Your search criteria matched only one product, shown below

BSV18X-XY



- Expanded wire entry designed to accommodate wire with a larger insulation thickness
- Designed to splice two solid or stranded wires together to repair or lengthen wires
- Brazed seam protects terminal barrel from splitting during the crimp process
- Internal wire stop assures proper length of insertion into terminal barrel
- UL Flammability UL 94V -0, maximum insulation temperature 221°F (105°C)
- UL and CSA rated up to 600 V per UL 486C

Part Number	BSV18X-XY
RoHS Compliancy Status	Compliant
Note	BSV18X-XY replaces BSV18X-X
Part Description	Butt Splice, 22– 18 AWG, vinyl insulated.
Product Type	Splices
CSA Certified	Yes
UL Listed	Yes
Length (In.)	1.03
Length (mm)	26.2
CE Compliant	No
Insulation	Vinyl
Max. Ins.	0.170
Max. Ins. (mm)	4.3
Panduit Color Code	Red
Plating Type	Tinned
Pricing Description	Butt Splice, vinyl insulated, 22- 18 AWG
Temperature Rating	221 Degrees Fahrenheit (105 Degrees Celsius)
Tool	CT-100A, CT-600-A, CT-1550, CT-1551, CT-2500
Wire Range	22 – 18 AWG
Wire Range (mm ²)	0.5 – 1.5
Min. Order UOM	CTN
Min. Order Qty.	100
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.