



Consolidation Point Boxes

- Suitable for wall mount and underfloor applications
- UL 2043 approved for use in air-handling spaces for copper applications
- Accept Mini-Com[®] Modules for STP and UTP, fiber optic, and audio/video, which snap in and out for easy moves, adds, and changes
- Supplied with cable management accessories
- Optional fiber conversion kit available

**CUFMB24BL****CUFB48BL**

Part Number	Part Description	Std. Pkg. Qty.	Std. Ctn. Qty.
CUFMB24BL	24-port aluminum underfloor consolidation point box includes pre-printed numbered labels with writable surface on back when pre-numbered labels are not applicable. Dimensions: 1.69"H x 10.85" W x 10.67"L (42.9mm x 275.6mm x 271.0mm).	1	—
CUFB48BL	48-port underfloor consolidation point box made of 16 gauge rugged steel for long term durability. Dimensions: 1.63"H x 10.00" W x 14.88"L (41.4mm x 254.0mm x 378.0mm).	1	—
CUFF-KIT	Optional fiber conversion kit to be used with CUFMB24BL and CUFB48BL. Kit includes: four Panduit [®] Pan-Ty [®] Cable Ties, four wire saddles, two adhesive fiber spools, two support brackets to hold fiber cable, one grounding lug, one laser warning label, one fiber warning label and two rubber grommets.	1	10



PanZone[®] Work Area Raised Floor Consolidation Point Enclosures

- Work with standard office raised floor tiles
- Include Cool Boot[®] Raised Floor Air Sealing Grommet for quick moves, adds, and changes
- Accept all Mini-Com[®] Modules
- Accept field terminated or pre-terminated connectivity solutions
- Secure lockable cover



Part Number	Part Description	Std. Pkg. Qty.
ACE48	Fully assembled office raised floor consolidation point enclosure mounts in 10.5" x 10.5" cutout in one raised floor tile; black finish. Support 48 copper cables or up to 96 fiber cables, accepts Mini-Com [®] Modules. Dimensions: 12.37"H x 12.45"W x 7.88"D (314mm x 316mm x 200mm)	1

PanZone[®] Overhead Distribution Racks

- Ideal solution for adding more rack spaces above racks or cabinets in data centers or telecommunication rooms
- Universal mounting bracket can be mounted to most industry ladder racks, wire basket, or suspended by threaded rod from ceiling
- Multiple mounting configurations
- 40/60/80 lbs. load rating
- Optional cable management solutions (PZBR4 and CMVDR2)

**PZLRB6**

Part Number	Part Description	Std. Pkg. Qty.
PZLRB2	2 RU ladder rack bracket. Dimensions: 8.75"H x 20.26"W x 3.26"D (222.3mm x 514.6mm x 82.8mm).	1
PZLRB4	4 RU ladder rack bracket. Dimensions: 12.25"H x 20.26"W x 3.26"D (311.2mm x 514.6mm x 82.8mm).	1
PZLRB6	6 RU ladder rack bracket. Dimensions: 15.75"H x 20.26"W x 3.26"D (400.1mm x 514.6mm x 82.8mm).	1

One rack space = 1.75" (44.45mm).