



Current refinements (click to remove)

[Search Tips](#)

[Region](#) **USA** [Product Family](#) **Female Metric Disconnect, Fully Insulated Nylon – Funnel Entry** [Text Search](#): 'DMNF2-488FIB-M'

Your search criteria matched only one product, shown below.



- Disconnect can be inserted and removed from the male tab without the use of tools for lower installed cost
- Fully insulated design provides protection from electrical shorts
- Disconnects available in common industry tab sizes
- Internal wire stop assures proper length of insertion into terminal barrel, providing a higher quality connection

Part Number:	DMNF2-488FIB-M
RoHS Compliancy Status:	Compliant
Part Description:	Metric Female Disconnect, 1.5 – 2.5mm ² wire range, 4.8mm x .8mm tab size, nylon fully insulated, funnel entry.
Height (mm):	5.5
Length (mm):	19.8
Width (mm):	7.9
Max. Ins.:	4.06
Panduit Color Code:	Blue
Tab Size (mm):	4.8 x 0.8
Tool:	CT-1525
Wire Range (mm ²):	1.5 – 2.5
Min. Order UOM:	PC

Min. Order Qty.: 1000

BOM Qty. (# of Pkgs.)

Add to My Catalog

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'My Catalog' features.

[legal information](#) | [privacy policy](#) | [site map](#)

Copyright © 1995-2007, PANDUIT CORP. All rights reserved.