

Search Results

- Evaluate
 - FAQ's
- Design a Solution
 - Part Drawings
 - PDFMTP Fiber Op ..
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips  Within Results


 Text Search: 'F96D5-5M10Y'

Your search criteria matched only one product, shown below

F96D5-5M10Y



- Pass all TIA/EIA-568-B.3 performance requirements
 - FOCIS-5 compliant
 - 100% factory inspected end face geometry (SC, ST, and FJ® end faces are 100% inspected in compliance with Telcordia GR -326-CORE, Issue 3)
 - Insertion loss per mated pair: 0.50dB typical; 0.75dB max.
 - 8-degree APC polish (55dB minimum Return Loss) on singlemode MTP* and UPC polish (55dB minimum Return Loss) on singlemode SC, ST, and FJ ® satisfy high-speed network application requirements
 - Factory terminated and 100% tested for insertion loss and return loss
 - Insertion loss and return loss data recorded for every singlemode cable assembly
 - Lifetime traceability of test data to a Q.C. number on each cable assembly
- * MTP is a registered trademark of US Conec Ltd.

Part Number	F96D5-5M10Y
RoHS Compliancy Status	Compliant
Note	F96D5-5M10Y replaces F96D5-5M10
Part Description	Female MTP* to female MTP* fiber interconnect cable assembly (one female MTP* connector on each end on ribbon interconnect cable) – 9/125µm.
Product Type	MTP* Interconnect Cable Assemblies
Length (m)	10
Fiber Compatibility	9/125µm
Fiber Type	Singlemode
Connector 1 Type	MTP* Connector
Connector 2 Type	MTP* Connector
End Configurations	MTP* to MTP*
Fiber Count	6
Pricing Description	PC 6-Fiber Singlemode MTPMTP* 9µm 10m
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.