


Search Results

- Evaluate
 - FAQ's
- Design a Solution
 - Part Drawings
 - DWG-Mini-Com FJ ..
 - PDF-Mini-Com FJ ..
 - DXF-Mini-Com FJ ..
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips  Within Results

 Text Search: 'FJJGM5COR'

Your search criteria matched only one product, shown below

FJJGM5COR



- TIA/EIA604 FOCIS-6 compliant connectors
- Exceed TIA/EIA568-B.3 requirements
- Insertion loss: 0.1dB average (multimode), 0.2dB average (singlemode)
- Return loss: >20dB (multimode), >40dB (singlemode)
- RJ45 small form factor duplex jack module -- double the port density in one module space
- Non-optical disconnect maintains data transmission under tensile loads for jacketed cable
- *Mini-Com*® Jack Modules snap in and out of all *Mini-Com*® telecommunications room products and work area outlets
- Each duplex jack module includes housing, cover, two ferrule assemblies, two crimp sleeves, one boot for 900 μ m buffered fiber, one boot for 3mm jacketed cable and one dust cap
- Can be clearly identified with labels and icons
- Fiber cable type: tight-buffered recommended
- Fiber cable size: 900 μ m buffered fiber, 3.0mm jacketed cable or 1.6mm – 2.0mm jacketed cable (noted in part description)

- For 250 μ m coated fiber termination, use 250 micron fiber build -up tube kit or fan-out kits
- Ferrule type: 2.5mm zirconia ceramic (highest durability for repeated matings)
- Field polish termination -- *PANDUIT*® recommends anaerobic adhesive
- Use field polish termination kit (FJKITG)

Part Number	FJJGM5COR
RoHS Compliancy Status	Compliant
Part Description	FJ® Multimode Duplex Fiber Optic Jack Module with phosphor bronze split sleeves for 3.0mm jacketed cable or 900 μ m buffered fiber installation.
Product Type	FJ® Jack Modules
Color	Orange
Fiber Compatibility	62.5/125 μ m / 50/125 μ m
Fiber Cable Size	3mm or 900 μ m
Fiber Cable Type	Tight-buffered recommended
Fiber Type	Multimode
Termination Style	Field Polish
Ferrule Type	Zirconia Ceramic
No. of Module Spaces	1
Pricing Description	FJ Jack Module Multimode for 3mm Jacketed Cable or 900 μ m Buffered Fiber OR
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.