Search Results

Evaluate
- Advertisements
  - PDF-Highest Perf..
- FAQ's
- Product Bulletins
  - PDF-Direct Buria..
- Videos
  - WMV-Panduit Comp..

Design a Solution
- Catalog Cut Sheet
  - PDF-GCE1/0-1/0 P
- Part Drawings
  - DWG-2-D cad for ..
  - PDF-E Style Grou..
  - DWG-3-D cad for ..

How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Install & Maintain
- Installation Instructions
  - PDF-Direct Buria..

Home > Products Overview > Search Results >

Current refinements (click ☒ to remove) Search Tips

☒ **Text Search: 'GCE250-1/0'**

Your search criteria matched only one product, shown below

GCE250-1/0

- Wide range-taking ability and multi-conductor design provide flexibility with a minimum number of parts, allowing for conductor to conductor, conductor to rebar, and conductor to ground rod applications
- Designed for the enhanced crimp process using patent pending technology meets IEEE Std 837™ – 2002
- Slotted design allows quick and easy assembly of conductor to connector using Panduit cable ties, included
- Pre-applied conductive antioxidant compound ensures a high quality mechanical and electrical bond, speeding installation
- Color-coded and marked with Panduit die index numbers for proper crimp die selection
- UL 467 Listed and CSA 22.2 Certified for grounding and bonding suitable for direct burial in earth or concrete when crimped with Panduit or industry standard crimping tools and Panduit dies
- Complies with vibration tests per MIL-STD-202G (METHOD 201A)

Part Number	GCE250-1/0
RoHS Compliancy Status	Compliant
Part Description	"E" style grounding connector for 1/0 STR – 250 kcmil (70 – 120mm²) main and #6 SOL – 1/0 STR tap (16 – 50mm²) tap.
CSA Certified	Yes
UL Listed	Yes
Height (In.)	2.18
Height (mm)	55.4
Length (In.)	1.00
Length (mm)	25.4
Width (In.)	1.05
Width (mm)	26.7
Copper Conductor Size Run	1/0 STR – 250 kcmil
Copper Conductor Size Tap	#6 SOL – 1/0 STR
CE Compliant	No
Copper Conductor Size Run (mm²)	(70 – 120)
Copper Conductor Size Tap (mm²)	(16 – 50)
Copper Lightning Conductor Size Range Run	59.5 kcmil
Ground Rod Size Tap (In.)	—
Panduit Color Code	Black
Panduit Die Index No.	PG25
Pricing Description	Ground "E" Style Connector, 1/0 STR-250 kcmil (70-120mm²) main and #6 SOL-1/0 STR tap (16-50mm²) tap
Rebar Size Run (In.)	3/8 – 1/2, #3 – #4
Rebar Size Tap (In.)	—
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	e

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

Copyright © 1995-2011, PANDUIT CORP. All rights reserved. | Legal Information | Privacy Policy