



enabling technologies

10 Gig Ethernet
Data Centers
Fiber System Deployment
Grounding System for Data Centers
Industrial Ethernet
Managing the Physical Layer
Network Security
Power Over Ethernet

product information

Products
Bill of Material
My Catalog
Part Search
Cross Reference
FAQ's
Download / Request Literature
Downloads

resources to help you

Evaluate Technologies
Design a Solution
How to Buy
Evaluate, Design & Install Products
Download Panduit Logo
White Papers
RoHS Compliance

value added services

Strategic Alliance Program
Consultants
Distributors
Installers
System Integrators
Warranties

Product Information: Products

USA | Cable Ties | Hook and Loop Cable Ties | Hook and Loop Cable Ties |

HLM / HLS Strips and Rolls



- Strip Ties (HLS / HLSP) - Rolls performed in convenient 6", 12" and 18" strips
- 15' & 75' Rolls (HLM / HLS-15 & 75) - Can be cut to desired length, eliminating waste
- Adjustable, releasable and reusable hundreds of times
- No waste since excess can be wrapped around bundle
- Operating temperature range: 0 to 220°F

HLSP in black and maroon are UL Listed for use in air handling spaces (Plenum) per NEC and are UL94V-2 flame rated

Note: Minimum 2" overlap required to achieve loop tensile rating

| | |
|-----------------------------------|---|
| Part Number | HLS-75R6 |
| Product Family | HLM / HLS Strips and Rolls |
| RoHS Compliant | Compliant |
| Part Description | Tak-Ty® Hook & Loop Cable Tie, 75' roll, .75" width, Standard, Blue |
| Product Type | Cable Ties |
| Material | Nylon Loop, Polyethylene Hook |
| Color | Blue |
| UL Listed (File #E56854) | No |
| Length (In.) | 900.0 |
| Length (mm) | 22,860 |
| Width (In.) | .750 |
| Width (mm) | 19.1 |
| Cross Section | Standard |
| Locking Style | Hook & Loop |
| Max. Bundle Dia. (mm) | Various |
| Max. Bundle Diameter (In.) | Various |
| Min. Bundle Diameter (In.) | .25 |
| Min. Bundle Diameter (mm) | 6 |
| Min. Loop Tensile Str. (N) | 222 |
| Min. Loop Tensile Strength (Lbs.) | 50 |
| Std. Pkg. UOM | EA |
| Thickness (In.) | .10 |
| Thickness (mm) | 2.5 |
| UOM | RL |
| Std. Pkg. Qty. | 1 |

evaluate

FAQs

design a solution

Part Drawings

install & maintain

related products

- Tak-Ty® Hook & Loop Cable Tie Mounts
- Tak-Ty® Hook & Loop Cable Tie Mounts- Screw Applied
- 4-Way Mounts Without Adhesive

Min. Order Qty 1

BOM Qty. (# of Pkgs.)

Add to My Catalog

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'My Catalog' features.

[legal information](#) | [privacy policy](#) | [site map](#)

Copyright © 1995-2005, PANDUIT CORP. All rights reserved.