



support | locate distributor | about panduit | c

*World Leader in Network and Electrical Solutions*

HOME | SOLUTIONS | RESOURCES | PRODUCTS | SERVICES | LEARNING

SEARCH

Current refinements (click  to remove)

Region **USA**  Product Family **HSTT Heat Shrink 4 ft. Pieces**  Text Search: 'HSTT05-48-Q5'

**Your search criteria matched only one product, shown below.**



- Shrink ratio of 2:1 insulates a wide range of diameters and irregular shapes
- Cross-linked, UV resistant material improves flame retardancy, chemical, and tempera

For clear, add "C" to end of part number package suffix (Example HSTT05-48-QC). Cor service for additional color information.

^ Meets Mil Spec AMS-DTL-23053/5 Class 1 (Colors), Class 2 (Clear)

Part Number:	HSTT05-48-Q5
RoHS Compliancy Status:	Compliant
Part Description:	Thin Wall Polyolefin Heat Shrink
Material:	Flame retardant polyolefin cross-linked except clear*
Color:	Green
CSA Certified:	Yes
Military Specification:	AMS-DTL-23053/5 Class 1
UL Recognized:	E122770
Length (ft.):	4
Length (m):	1.2
Flammability Rating:	Flame Retardant
Max. Recovered I.D. (In.):	.023
Max. Recovered I.D. (mm):	.6
Min. Expanded I.D. (In.):	.046
Min. Expanded I.D. (mm):	1.2
Nominal Diameter / Size:	3/64
Nominal Recovered Wall Thickness (In.):	.016
Nominal Recovered Wall Thickness (mm):	.4
Shrink Ratio:	2:1
Temperature Range:	-67°F to 275°F (-55°C to 135°C)
Min. Order UOM:	PC
Min. Order Qty.:	25
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to My Catalog	<input type="checkbox"/>

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'My Catalog' features.

[legal information](#) | [privacy policy](#) | [site map](#)

---

Copyright © 1995-2007, PANDUIT CORP. All rights reserved.