



Network and Electrical Solutions
UNIFIED PHYSICAL INFRASTRUCTURESM

Worldwide |



[Home](#)

[Industries](#)

[Solutions](#)

[Products](#)

[Partners](#)

[Support](#)

[About Us](#)

[Careers](#)

[Entire Site](#)

Search Results

Evaluate

- FAQ's

How to Buy

- Bill of Material

- Favorite Products List

- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click to remove) [Search Tips](#) Within Results

Text Search: 'HSTT09-C5'

Your search criteria matched only one product, shown below

HSTT09-C5



Flexible Polyolefin DRY-SHRINK™ Heat Shrink Tubing

- General Purpose heat shrink tubing for dry locations
- Applications include insulating, protecting, harnessing and identifying wires.
- Material Type: Crosslinked Polyolefin
- Shrink Ratio: 2:1
- Temperature Range: -67°F to 275°F (-55°C to 135°C)
- Flammability Rating: Flame retardant EXCEPT clear
- Voltage: 600 V
- UL Recognized, CSA Certified
- Mil Spec: AMS-DTL-23053/5 Class 1 (Colors) Class 2 (Clear)

- Part Number
- RoHS Compliancy Status
- Part Description
- Material
- Color
- CSA Certified
- Military Specification

HSTT09-C5

Compliant

Thin Wall Polyolefin Heat Shrink

Polyolefin cross-linked

Green

Yes

AMS-DTL-23053/5 Class 1

▪ UL Recognized	E122770
▪ Flammability Rating	Flame Retardant
▪ Length Per Reel (ft.)	100
▪ Length Per Reel (m)	30.5
▪ Max. Recovered I.D. (In.)	.046
▪ Max. Recovered I.D. (mm)	1.2
▪ Min. Expanded I.D. (In.)	.093
▪ Min. Expanded I.D. (mm)	2.4
▪ Nominal Diameter / Size	.093
▪ Nominal Recovered Wall Thickness (In.)	.020
▪ Nominal Recovered Wall Thickness (mm)	.5
▪ Pricing Description	Heat Shrink Thin, .09"(2.4mm) Dia, Green
▪ Shrink Ratio	2:1
▪ Temperature Range	-67°F to 275°F (-55°C to 135°C)
▪ Min. Order UOM	RL
▪ Min. Order Qty.	1
▪ BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
▪ Add to Favorite Product List	<input type="checkbox"/>

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

Home | Industries | Solutions | Products | Partners | Support | Contact Us | Site Map | Careers
 Copyright © 1995-2008, PANDUIT CORP. All rights reserved. | [Legal Information](#) | [Privacy Policy](#)