



## enabling technologies

[10 Gig Ethernet](#)  
[Data Centers](#)  
[Fiber System Deployment](#)  
[Grounding System for Data Centers](#)  
[Industrial Ethernet](#)  
[Managing the Physical Layer](#)  
[Network Security](#)  
[Power Over Ethernet](#)

## product information

[Products](#)  
[Bill of Material](#)  
[My Catalog](#)  
[Part Search](#)  
[Cross Reference](#)  
[FAQ's](#)  
[Download / Request Literature](#)  
[Downloads](#)

## resources to help you

[Evaluate Technologies](#)  
[Design a Solution](#)  
[How to Buy](#)  
[Evaluate, Design & Install Products](#)  
[Download Panduit Logo](#)  
[White Papers](#)  
[RoHS Compliance](#)

## value added services

[Strategic Alliance Program](#)  
[Consultants](#)  
[Distributors](#)  
[Installers](#)  
[System Integrators](#)  
[Warranties](#)

## Product Information: Products

[USA](#) | [Heat Shrink & Abrasion Protection](#) | [Heat Shrink](#) | [General Purpose, Flexible Polyolefin for Dry Locations](#) |

### HSTT Heat Shrink 4 ft (1.2M) Pieces



## evaluate

[FAQs](#)

## design a solution

## install & maintain

- Shrink ratio of 2:1 insulates a wide range of diameters and irregular shapes
- Cross-linked, UV resistant material improves flame retardancy, chemical, and temperature resistance

For clear, add "C" to end of part number package suffix (Example HSTT05-48-QC). Contact customer service for additional color information.

^ Meets Mil Spec AMS-DTL-23053/5 Class 1.

|                                        |                                                       |
|----------------------------------------|-------------------------------------------------------|
| Part Number                            | HSTT25-48-Q                                           |
| Product Family                         | HSTT Heat Shrink 4 ft (1.2M) Pieces                   |
| RoHS Compliant                         | Compliant                                             |
| Part Description                       | Thin Wall Polyolefin Heat Shrink                      |
| Material                               | Flame retardant polyolefin cross-linked except clear^ |
| Color                                  | Black‡                                                |
| CSA Certified                          | Yes                                                   |
| Military Specification                 | AMS-DTL-23053/5 Class 1                               |
| UL Recognized                          | E122770                                               |
| Length (Ft.)                           | 4                                                     |
| Flammability Rating                    | Flame Retardant                                       |
| Max. Recovered I.D. (In.)              | .125                                                  |
| Max. Recovered I.D. (mm)               | 3.2                                                   |
| Min. Expanded I.D. (In.)               | .250                                                  |
| Min. Expanded I.D. (mm)                | 6.4                                                   |
| Nominal Diameter / Size                | 1/4                                                   |
| Nominal Recovered Wall Thickness (In.) | .025                                                  |
| Nominal Recovered Wall Thickness (mm)  | .6                                                    |
| Shrink Ratio                           | 2:1                                                   |
| Std. Pkg. UOM                          | PK                                                    |
| Temperature Range                      | -67°F to 275°F (-55°C to 135°C)                       |
| UOM                                    | PC                                                    |

|                       |    |
|-----------------------|----|
| Std. Pkg. Qty.        | 25 |
| Min. Order Qty        | 25 |
| BOM Qty. (# of Pkgs.) |    |

Add to My Catalog

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'My Catalog' features.

[legal information](#) | [privacy policy](#) | [site map](#)

Copyright © 1995-2005, PANDUIT CORP. All rights reserved.