

Search Results

Evaluate

- FAQ's

How to Buy

- Bill of Material

- Favorite Products List

- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips

 Text Search: 'HSTTV12-M6'

Your search criteria matched only one product, shown below

## HSTTV12-M6



Flexible Polyolefin VW-1 DRY-SHRINK™ Heat Shrink Tubing in Bulk Reels

- For dry locations
- Highly flame retardant Meets UL VW-1 Rating
- Fast Shrink Time
- Material Type: Highly Flexible Crosslinked Polyolefin
- Shrink Ratio: 2:1
- Temperature Range: -67°F to 257°F (-55°C to 125°C)
- Voltage: 600V
- UL VW-1 Recognized, CSA Certified
- Mil Spec: AMSDTL-23053/5 Class 3

Part Number	HSTTV12M6
RoHS Compliancy Status	Compliant
Part Description	Thin Wall Polyolefin Heat Shrink (UL224 VW1)
Material	Polyolefin cross-linked
Color	Blue
CSA Certified	Yes
Military Specification	AMS-DTL-23053/5 Class 3
UL Recognized	E122770
Length (m)	304.8
CE Compliant	No
CE Marking	No
Flammability Rating	UL224 VW-1
Length Per Reel (ft.)	1000
Length Per Reel (m)	304.8
Max. Recovered I.D. (In.)	.062
Max. Recovered I.D. (mm)	1.6
Min. Expanded I.D. (In.)	.125
Min. Expanded I.D. (mm)	3.2
Nominal Diameter (In.)	.125
Nominal Diameter (mm)	3.2
Nominal Recovered Wall Thickness (In.)	.02
Nominal Recovered Wall Thickness (mm)	0.5
Pricing Description	Heat Shrink Thin VW1, .12"(3.2mm) Dia, Blue
Shrink Ratio	2:1
Temperature Range	-67°F to 257°F (-55°C to 125°C)
Min. Order UOM	RL
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.