


Search Results

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
  - Favorite Products List
  - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips

 Text Search: 'LCC6-14W-L'

Your search criteria matched only one product, shown below

### LCC6-14W-L



For Use with Stranded Copper Conductors

- Long barrel maximizes number of crimps and provides premium wire pull -out strength and electrical performance
- Inspection window to visually assure full conductor insertion
- Color-coded barrels marked with *PANDUIT* and specified competitor die index numbers for proper crimp die selection
- Tin-plated to inhibit corrosion
- UL Listed and CSA Certified to 35 KV\*\* and temperature rated to 90°C when crimped with *PANDUIT* and specified competitor crimping tools and dies
- UL Listed and CSA Certified for wide wire range -taking capability when crimped with *PANDUIT® Uni-Die™* Dieless Crimping Tools‡
- **Tested by Telcordia – meets NEBS Level 3**
- Meets J-STD-607-A and TIA-942 requirements for network systems grounding applications
- Available with NEMA hole sizes and spacing

Note: These code conductor lugs are manufactured for use with AWG wire only.

Part Number	LCC6-14W-L
RoHS Compliancy Status	Compliant
Part Description	Two-hole, long barrel lug with window, #6 AWG, 1/4" stud hole, 1.75" hole spacing.
CSA Certified	Yes
UL Listed	Yes
Length (In.)	3.61
Length (mm)	91.7
Copper Conductor Size	#6 AWG
Stud Hole Size (In.)	1/4
Stud Hole Spacing (In.)	1.75
Tongue Width (In.)	.48
Barrel Length (In.)	1.07
Angle	Straight
Barrel Length (mm)	27.2
CE Compliant	No
CE Marking	No
Figure No.	1
Panduit Color Code	Blue
Panduit Die Index No.	P24
Pricing Description	Copper Comp. Lug, 2 Hole, #6 AWG, 1/4" (6.4mm) Stud, 1.75" (44.4mm) Hole Spacing
Stud Hole Size (mm)	M6
Tongue Thickness	.08
Tongue Type	Standard
Tongue Width (mm)	12.2
Tool	CT-1700, CT-930, CT-2931
Wire Range (mm <sup>2</sup> )	16
Wire Strip Length (In.)	1 1/8
Wire Strip Length (mm)	29.0
Min. Order UOM	PC
Min. Order Qty.	1
Burndy Die Index No.	7
T&B Die Index No.	24
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.