

Products

Products Overview

Product Search

Evaluate

- FAQ's
- Press Releases
- PANDUIT Term.
- Product Bulletins
- PDFMetric Lugs ..

Design a Solution

- Catalog Cut Sheet
- PDFLCMA6-5-C Pr
- Part Drawings
- PDFMetric One-H ..

How to Buy

- Bill of Material
- Favorite Products List
- Locate Distributor

Install & Maintain

- Installation Instructions
- PDFMetric Lugs ..

Home > Products Overview > Product Search >

Current refinements (click  to remove) Search Tips

Part Number > LCMA185-16-X


Your search criteria matched only one product, shown below

LCMA185-16-X



For Use with Class 2 Stranded Copper Conductors

- Inspection window to visually assure full conductor insertion
- Tin-plated to inhibit corrosion
- UL Listed, UL Recognized, and CSA Certified to 35 KV** and temperature rated to 90°C when crimped with Panduit tools and dies
- Product information marked on connector for selection and installation
- Rounded tongue convenient for use in tight spaces
- Internally beveled wire entry for fast and easy installation

Part Number	LCMA185-16-X
RoHS Compliancy Status	Compliant
Part Description	Metric conductor, one-hole, standard barrel with window lug.
Product Type	Compression Connectors- Metric Lugs
CSA Certified	Yes
UL Listed	Yes
Length (mm)	72.5
Angle	Straight
Barrel I.D. (mm)	18.6
Barrel Length (mm)	28.2
CE Compliant	No
Copper Conductor Size Class 2 (mm2)	185
Figure No.	1
Hole Diameter (mm)	18.0
Palm Width (mm)	33.5
Panduit Die Index No.	P76
Pricing Description	Copper Compression Metric Lug, 1 Hole, 185mm ² Wire, M16 Stud
Stud Hole Size (mm)	M16
Stud Set Back (mm)	17.5
Tongue Type	Standard
Wire Strip Length (mm)	29.7
Wrench Clearance (mm)	16.5
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.