

Search Results
Evaluate

- FAQ's

Design a Solution

 - Catalog Cut Sheet
 - PDF-P18-6RHT6-C
 - Part Drawings
 - PDF-Ring Termina ..

How to Buy

 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

 Current refinements (click to remove) [Search Tips](#)
 Text Search: 'P6-56RHT6-E'

Your search criteria matched only one product, shown below

P6-56RHT6-E


- Nickel plated copper for temperatures up to 650°F (343°C)
- Internal barrel serrations assure good wire contact and maximum tensile strength
- Brazed seam protects terminal barrel from splitting during the crimp process
- Barrel of terminal internally beveled to provide quick and easy wire insertion
- Rated up to 2000 V

Part Number	P6-56RHT6-E
RoHS Compliancy Status	Compliant
Part Description	High Temperature Ring Terminal, 6 AWG, 5/16" stud size, non-insulated.
Product Type	Terminals
CSA Certified	Pending
UL Listed	Yes
Length (In.)	1.33
Length (mm)	33.8
Width (In.)	0.62
Width (mm)	15.8
CE Compliant	No
Clearance	0.51
Clearance (mm)	13.0
Insulation	Non-Insulated
Panduit Color Code	No Color Non-Insulated
Plating Type	Nickel
Pricing Description	Ring Terminal, high temperature, non-insulated, 6 awg, 5/16" stud size
Stock	0.05
Stock (mm)	1.1
Stud Size	5/16"
Temperature Rating	650 Degrees Fahrenheit (343 Degrees Celsius)
Tool	CT-2600, CD-2600-6†
Wire Range	6 AWG
Wire Range (mm ²)	16
Min. Order UOM	PC
Min. Order Qty.	20
BOM Qty. (# of Pkgs.)	

-
- Add to Favorite Product List

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

[Home](#) | [Industries](#) | [Solutions](#) | [Services](#) | [Products](#) | [Partners](#) | [Support](#) | [Contact Us](#) | [Site Map](#) | [Careers](#)
Copyright © 1995-2011, PANDUIT CORP. All rights reserved. | [Legal Information](#) | [Privacy Policy](#)