



Current refinements (click  to remove)

[Search Tips](#)

Region USA  Product Family HLM / HLS Hook & Loop Strips and R

Your search criteria matched only one product, shown below.

**Related Products**

[Click here to see ima](#)

- Strip Ties (HLS) Rolls performed in convenient 6", 12 18" strips
- 15' & 75' Rolls (HLM/HLS 5 & 75)- Can be cut to desire length, eliminating waste
- Adjustable, releasable, and reusable hundreds of times for applications requiring frequent moves, adds, or chan
- Hook and loop material maintains network data integrit protecting against overensioning of high performance cop and fiber cables
- Easy to use and operator safe with no sharp edges
- Complementary mounts available

- [Tak-Ty Hook & Loop Cable Ti...](#)
- [Tak-Ty Hook & Loop Cable Ti...](#)
- [4-Way Adhesive Backed Cable Tie Mou...](#)
- [Flat Pan-Post™ Standof...](#)
- [Extra-Heavy Cable Tie Mounts](#)
- [Swivel Mounts](#)
- [More...](#)

Note: Minimum 2" overlap required to achieve loop tensi

Part Number:	HLM-15R4
RoHS Compliancy Status:	Compliant
Part Description:	Hook & Loop Cable Tie, 15' roll, Miniature cross section
Product Type:	Cable Ties
Material:	Nylon Loop, Polyethylene Hook
Color:	Yellow
CSA Certified:	No
UL Listed (File #E56854):	No
UL Recognized (File #E56854)	No
Length (ft.):	15.0
Length (In.):	180.0
Length (m):	4.6
Length (mm):	4572
Width (In.):	.330
Width (mm):	8.4
CE Compliant:	Yes
Cross Section:	Miniature
Locking Style:	Hook & Loop
Max. Bundle Diameter (In.):	Various
Max. Bundle Diameter (mm):	Various
Min. Loop Tensile Strength (L	18
Min. Loop Tensile Strength (N	80
Temperature Range:	0°F to 220°F
Thickness (In.):	.10
Thickness (mm):	2.5
Min. Order UOM:	RL
Min. Order Qty.:	1
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to My Catalog	<input type="checkbox"/>

Please [registe](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'My Catalog' f