

Search Results

Evaluate

- FAQ's

How to Buy

- Bill of Material

- Favorite Products List

- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips  Within Results


 Text Search: 'HSECFR0.5X'

Your search criteria matched only one product, shown below

HSECFR0.5-X



- Heat indicating line ensures correct temperature is applied
- Cross -linked, UV resistant material improves flame retardancy, chemical, and temperature resistance
- Shrink ratio of 3:1 insulates a wide range of diameters and irregular shapes, which reduces inventory costs
- * Flame retardant products are manufactured from a material that is rated UL94V -0.

Part Number	HSECFR0.5X
RoHS Compliancy Status	If RoHS Decabrome Free Part required use HSECFR0.5Y
Note	Call Customer Service for Pricing, Availability, etc.
Part Description	Flame Retardant Thick Wall End Caps
Material	Flame retardant cross-linked polyolefin with adhesive
Color	Black
Copper Conductor Size Range	#8 – #6 AWG
Cap Length (In.)	3.00
Cap Length (mm)	76.2
Conductor Size Range (mm ²)	10 to 25
Max. Recovered I.D. (In.)	.16
Max. Recovered I.D. (mm)	4.1
Min. Expanded I.D. (In.)	.51
Min. Expanded I.D. (mm)	13.0
Nominal Recovered Wall Thickness (In.)	.090
Nominal Recovered Wall Thickness (mm)	2.4
Pricing Description	Heat Shrink Thick Adhesive End Cap, .5"(13mm)
Temperature Range	-67°F to 230°F (-55°C to 110°C)
Min. Order UOM	PC
Min. Order Qty.	10
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.