

Search Results

- Evaluate
 - FAQ's
- Design a Solution
 - Part Draw ings
 - PDF-Service Post ..
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips  Within Results

 Text Search: 'SP2-2/0-Q'


Your search criteria matched only one product, shown below

SP2-2/0-Q



Male - Two Cables

- For grounding two copper code conductors to steel structures, busbars, or transformers or for tapping from busbar with hex nut and washer
- Made from high copper content, hard drawn copper rod provides high strength
- Offered with standard and long stud lengths to accommodate a variety of mounting applications
- Wide wire range-taking capability minimizes inventory requirements
- True hex design for body and nut hex provides correct fit with socket, box, or open end wrenches resulting in proper torquing of electrical connection
- Pressure bar provides secure connection on a full range of conductor combinations used with each connector providing premium wire pull-out strength
- UL Listed for grounding and bonding and suitable for direct burial in earth or concrete

Part Number	SP2-2/0-Q
RoHS Compliancy Status	Compliant
Part Description	Bronze, service post connector, male, tw o cable, type SP2.
Product Type	Grounding Connectors - Service Post
UL Listed	Yes
Length (In.)	1.88
Length (mm)	47.8
Copper Conductor Size Range	#2 SOL – 2/0 STR
Body Hex	.88
Nut Hex	1.13
Pricing Description	Bronze Service Post Connector, #2 SOL-2/0 STR, male, 2 cables
Stud Length (In.)	.75
Stud Length (mm)	19.1
Stud Size	1/2 – 13
Tightening Torque (In-Lbs)	500
Wire Diameter Range (In.)	.258-.419
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.