

Search Results

- Evaluate
- FAQ's
  - Selection Guides
  - PDF Convenience..
- How to Buy
- Bill of Material
  - Favorite Products List
  - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips

 Text Search: 'PN10-10F-E'

Your search criteria matched only one product, shown below

**PN10-10F-E**



- Fork design provides for fast and easy installation, without the need to remove fastener
  - Metal insulation grip sleeve crimps to wire insulation, providing protection to the crimp joint during high vibration applications
  - Internal barrel serrations assure good wire contact and maximum tensile strength
  - UL Flammability UL 94V -2/HB, maximum insulation temperature 221°F (105°C)
  - UL and CSA rated up to 600 V per UL 486A/B, where applicable
- ‡UL and CSA approved tooling/product combinations.  
Note: Wire sizes #26 – #22 AWG, are not UL Listed or CSA Certified.

|                               |   |
|-------------------------------|---|
| Part Number                   | PN1010F-E   |
| RoHS Compliancy Status        | Compliant   |
| Part Description              | Fork Terminal, nylon insulated, 12- 10 AWG, #10 stud size.                          |
| Product Type                  | Terminals   |
| CSA Certified                 | Yes   |
| UL Listed                     | Yes   |
| Length (In.)                  | 1.04  |
| Length (mm)                   | 26.4  |
| Width (In.)                   | 0.37  |
| Width (mm)                    | 9.4   |
| CE Compliant                  | No  |
| Clearance                     | 0.22  |
| Clearance (mm)                | 5.6   |
| Insulation                    | Nylon   |
| Max. Ins.                     | 0.225   |
| Max. Ins. (mm)                | 5.75  |
| Panduit Color Code            | Yellow  |
| Plating Type                  | Tinned  |
| Pricing Description           | Terminal Convenience Package  |
| Stock                         | 0.04  |
| Stock (mm)                    | 1.0   |
| Stud Size                     | #10   |
| Temperature Rating            | 221 Degrees Fahrenheit (105 Degrees Celsius)  |
| Tool                          | CT-100A‡, CT-600-A‡, CT-1550‡, CT-1551‡, CT-2500‡                                   |
| Wire Range                    | 12 – 10 AWG   |
| Wire Range (mm <sup>2</sup> ) | 4.0 – 6.0   |
| Min. Order UOM                | PC  |
| Min. Order Qty.               | 20  |
| BOM Qty. (# of Pkgs.)         | <input type="text" value="0"/>  |
| Add to Favorite Product List  |  |

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.