

Search Results

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips


 Text Search: 'PNF14-10SLF-M'

Your search criteria matched only one product, shown below

PNF14-10SLF-M



- Locks in place for a secure connection in limited spaces
- Fork design provides for fast and easy installation, without the need to remove fastener
- Metal insulation grip sleeve crimps to wire insulation, providing protection to the crimp joint during high vibration applications
- Internal barrel serrations assure good wire contact and maximum tensile strength
- UL Flammability UL 94V -2/HB, maximum insulation temperature 221°F (105°C)
- UL and CSA rated up to 600 V per UL 486

▪ Part Number	PNF1410SLF-M
▪ RoHS Compliancy Status	Compliant
▪ Part Description	Short Locking Fork Terminal, 16- 14 AWG, #10 stud size, funnel entry, nylon insulated.
▪ Product Type	Terminals
▪ CSA Certified	Yes
▪ UL Listed	Yes
▪ Length (In.)	.81
▪ Length (mm)	20.6
▪ Width (In.)	.33
▪ Width (mm)	8.4
▪ Bolt Dia.	.70
▪ CE Compliant	No
▪ CE Marking	No
▪ Clearance	.23
▪ Clearance (mm)	5.8
▪ Max. Ins.	.162
▪ Panduit Color Code	Blue
▪ Pricing Description	Short Locking Fork Terminal, nylon insulated, 16 14 AWG, #10 stud size, funnel entry
▪ Stock	.03
▪ Stock (mm)	0.8
▪ Stud Size	#10
▪ Tool	CT-1550, CT-1551, CT-2500
▪ Wire Range	16 – 14 AWG
▪ Wire Range (mm ²)	1.0 – 2.5
▪ Min. Order UOM	PC
▪ Min. Order Qty.	1000
▪ BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
▪ Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.