


Search Results

- Evaluate
 - FAQ's
- Design a Solution
 - Catalog Cut Sheet
 - PDFPV8-8RX-QY P
 - PDFPV14-8RX-C P
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips


 Text Search: 'PV8-12RX-XY'

Your search criteria matched only one product, shown below

PV8-12RX-XY



- Ring tongue design assures a secure connection in high vibration applications
 - Expanded wire entry designed to accommodate wire with a larger insulation thickness
 - Insulation support helps to prevent wire damage in bending applications
 - Brazed seam protects terminal barrel from splitting during the crimp process
 - Internal barrel serrations assure good wire contact and maximum tensile strength
 - UL Flammability UL 94V -0, maximum insulation temperature 221°F (105°C)
 - UL rated up to 600 V per UL 486A/B
- ‡UL approved tooling/product combinations.

Part Number	PV8-12RX-XY
RoHS Compliancy Status	Compliant
Note	PV8-12RX-XY replaces PV8-12RX-QY
Part Description	Ring Terminal, large wire, 8 AWG, 1/2" stud size, vinyl expanded insulation.
Product Type	Terminals
CSA Certified	No
UL Listed	Yes
Length (In.)	1.74
Length (mm)	44.2
Width (In.)	0.82
Width (mm)	20.8
CE Compliant	No
Clearance	0.51
Clearance (mm)	13.0
Insulation	Vinyl
Max. Ins.	0.360
Max. Ins. (mm)	9.1
Panduit Color Code	Red
Plating Type	Tinned
Pricing Description	Ring Terminal, large wire, expanded vinyl insulation, 8 AWG, 1/2" stud size
Stock	0.04
Stock (mm)	1.0
Stud Hole Size (mm)	M12
Stud Size	1/2"
Temperature Rating	221 Degrees Fahrenheit (105 Degrees Celsius)
Tool	CT-720 With Die Insert CB720PV8-2‡, CT-2600 With Die Insert CB2600-PV8‡
Wire Range	8 AWG
Wire Range (mm²)	10.0
Min. Order UOM	PC
Min. Order Qty.	10
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.