

Search Results

- Evaluate
 - FAQ's
- Design a Solution
 - Part Drawings
 - PDF Braided Expa..
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips


 Text Search: 'SE250P-TR0'

Your search criteria matched only one product, shown below

SE250P-TR0



- Provides continuous abrasion resistance for wires cables, and tubing
- Lightweight durable protection
- Highly flexible open weave will not trap heat or humidity
- Rated for use up to 257°F (125°C)
- Allows for use with irregular shapes
- Stock colors: Black gray and white

Part Number	SE250PTR0
RoHS Compliancy Status	Compliant
Part Description	Braided Expandable Sleeving provides continuous abrasion resistance for wires, cables and tubing. The highly flexible open weave will not trap heat or humidity.
Product Type	Braided Expandable Sleeving
Material	Polyethylene Terephthalate
Color	Black
CSA Certified	Yes
UL Recognized	E116868
Length (m)	61.0
CE Compliant	No
Flammability Rating	HB
Length Per Reel (ft.)	200
Length Per Reel (m)	61.0
Nominal Diameter Range (In.)	1.75 – 3.64
Nominal Diameter Range (mm)	44.5 – 114.3
Nominal I.D. (In.)	2.50
Nominal I.D. (mm)	63.50
Pricing Description	Exp. Sleeving, 2.50" (63.5mm), Black
Temperature Range	-94°F – 257°F (-70°C – 125°C)
Type	Braided Expandable Sleeving
Min. Order UOM	RL
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.