



Representative

**Catalog Number:** E10731  
**Product ID:** 7TAI029620R0072  
**UPC Number:** 78621082963  
**EAN Number:** 05414363150398  
**Status:** Active

Non-Insulated Tubular Ring Terminal, Length 1.38 Inches, Width .60 Inches, Bolt Hole 3/8 Inch, Wire Range 6/6AN, Copper, Tin Plated

- These non-insulated ring terminals are made of electrolytic copper for high conductivity.
- They can be installed with crimping tools having a single indenter or double indenter (recommended for solid wire).
- Application Tools: WT115A, TBM6, TBM6S, WT3185

#### North American Specifications (UNSPSC)

|                  |                                                                                                                                                                                                               |
|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| UNSPSC           | 39121432 Electrical terminals                                                                                                                                                                                 |
| IGCC             | 4603 Electrical terminals                                                                                                                                                                                     |
| Brand Name       | Sta-Kon                                                                                                                                                                                                       |
| Type             | Ring Terminal                                                                                                                                                                                                 |
| Special Features | These non-insulated ring terminals are made of electrolytic copper for high conductivity. They can be installed with crimping tools having a single indenter or double indenter (recommended for solid wire). |
| Standard         | UL E9809                                                                                                                                                                                                      |
| Wire Size        | 6                                                                                                                                                                                                             |
| Voltage Rating   | 600V                                                                                                                                                                                                          |
| Material         | Copper                                                                                                                                                                                                        |
| Color            | Metallic                                                                                                                                                                                                      |

#### Packaging

|                           |                   |
|---------------------------|-------------------|
| Inner Quantity            | 200               |
| Inner Dimensions (inches) | 4x4x3             |
| Outer Quantity            | 2000              |
| Outer Dimensions (inches) | 3.6x3.2x3.2       |
| Weight Uom                | 1.19 lbs. per 100 |

#### Documents / Support Tools

|                             |                      |
|-----------------------------|----------------------|
| Technical Data Sheet CA     | Available on Website |
| Technical Data Sheet Global | wsd-000168           |

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
www.tnb.com

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:techsupport@tnb.com