

# XCKP2127N12

limit switch XCKP - th.plastic roller lever plung.  
Ver - 1NC+1NO - snap - 1/2NPT

Product availability: Stock - Normally stocked in distribution facility



## Main

|                               |  |
|-------------------------------|--|
| Commercial Status             | Commercialised                                   |
| Range of product              | OsiSense XC                                      |
| Series name                   | Standard format                                  |
| Product or component type     | Limit switch                                     |
| Device short name             | XCKP   |
| Sensor design                 | Compact form E conforming to CENELEC EN 50047    |
| Body type                     | Fixed  |
| Head type                     | Plunger head                                     |
| Material                      | Plastic  |
| Body material                 | Plastic  |
| Head material                 | Zamak  |
| Movement of operating head    | Linear   |
| Type of operator              | Spring return roller lever plunger thermoplastic |
| Type of approach              | Vertical approach                                |
| Number of poles               | 2  |
| Contacts type and composition | 1 NC + 1 NO                                      |
| Contacts operation            | Snap action                                      |

## Complementary

|  |   |
|--|---|
| Switch actuation                       | By 30° cam  |
| Electrical connection                  | Screw-clamp terminals, clamping capacity: 1 x 0.34...2 x 1.5 mm <sup>2</sup>  |
| Cable entry                            | 1 entry tapped for 1/2" NPT cable gland   |
| Contacts insulation form               | Zb  |
| Positive opening                       | With  |
| Positive opening minimum force         | 18 N  |
| Minimum force for tripping             | 6 N   |
| Maximum actuation speed                | 3.28 ft/s (1 m/s)   |
| Repeat accuracy                        | 0.1 mm on the tripping points with 1 million operating cycles   |
| Contact code designation               | Q300, DC-13 (Ue = 250 V, Ie = 0.27 A) conforming to EN/IEC 60947-5-1 appendix A<br>A300, AC-15 (Ue = 240 V, Ie = 3 A), Ithe = 10 A conforming to EN/IEC 60947-5-1 appendix A  |
| [Ui] rated insulation voltage          | 300 V conforming to CSA C22.2 No 14<br>500 V degree of pollution 3 conforming to IEC 60947-1<br>300 V conforming to UL 508  |
| Resistance across terminals            | <= 25 MOhm conforming to IEC 60255-7 category 3   |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to IEC 60947-1<br>6 kV conforming to IEC 60664  |
| Short circuit protection               | 10 A cartridge fuse gG  |
| Electrical durability                  | 5000000 cycles, DC-13, 48 V, 7 W, operating rate: <= 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 cycles, DC-13, 24 V, 10 W, operating rate: <= 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 cycles, DC-13, 120 V, 4 W, operating rate: <= 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C |
| Mechanical durability                  | 15000000 cycles   |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

|  |   |
|--|---|
| Shock resistance                           | 50 gn (duration = 11 ms) conforming to IEC 60068-2-27                                   |
| Vibration resistance                       | 25 gn (f = 10...500 Hz) conforming to IEC 60068-2-6                                     |
| IP degree of protection                    | IP67 conforming to IEC 60529<br>IP66 conforming to IEC 60529                            |
| IK degree of protection                    | IK04 conforming to EN 50102   |
| Class of protection against electric shock | Class II conforming to NF C 20-030<br>Class II  |
| Ambient air temperature for operation      | -13...158 °F (-25...70 °C)  |
| Ambient air temperature for storage        | -40...158 °F (-40...70 °C)  |
| Protective treatment                       | TC  |
| Product certifications                     | CCC<br>CSA<br>UL  |
| Standards                                  | EN 60204-1<br>EN 60947-5-1<br>IEC 60204-1<br>IEC 60947-5-1<br>UL 508<br>CSA C22.2 No 14 |

## Ordering and shipping details

|                       |   |
|-----------------------|---|
| Category              | 22418 - LIMIT SWITCH,IEC,XCKP&XCKT                |
| Discount Schedule     | T   |
| GTIN                  | 00785901269625                                    |
| Nbr. of units in pkg. | 1   |
| Package weight(Lbs)   | 0.70  |
| Product availability  | Stock - Normally stocked in distribution facility |
| Returnability         | Y   |
| Country of origin     | FR  |

## Offer Sustainability

|                               |   |
|-------------------------------|---|
| Sustainable offer status      | Not Green Premium product   |
| RoHS                          | Compliant - since 1037 - <a href="#">Schneider Electric declaration of conformity</a> |
| REACH                         | Reference not containing SVHC above the threshold                                     |
| Product environmental profile | Available <a href="#">Download Product Environmental</a>                              |

## Contractual warranty

|        |           |
|--------|-----------|
| Period | 18 months |
|--------|-----------|