



List Price \$92.00 USD

Availability **Stock Item: This item is normally stocked in our distribution facility.**

**Technical Characteristics**

Actuation	Vertical
Actuator Action	Momentary
Lever Arm Length	n/a
Actuator	Metal End Plunger (ZCE10)
Head Type	Top Plunger
Roller Dimension	n/a
Operating Torque/Force	8.5 Inch-Ounces (0.06Nm)
Maximum Actuation Speed	0.5 m/s
Degree of Protection	IP66/67/68
Operating Temperature Range	-13 to 158°F (-25 to 70°C)
Conforming to Standards	CENELEC EN 50047
Repeat Accuracy	0.05mm (on tripping points)
Body Type	Miniature Modular (ZCMD21)
Body Material	Zinc Alloy
Type	XCMD
RoHS	Yes
Positive Opening	Yes
Ampere Rating	6A
Connection Type	PVR Cable (3m)
Contact Configuration	1 N.O./1 N.C.
Shock Resistance	25G
Vibration Resistance	5G
Weight	0.730 lbs (0.330kg)
Contact Operation	Snap Action
Marketing Trade Name	OsiSense
Maximum Voltage Rating	240VAC/250VDC
NEMA Enclosure Rating	NEMA 1/2/4X/6/6P/12/13
Approvals	UL Listed - CSA Certified - CE Marked

**Shipping and Ordering**

Category	22418 - Limit Switches, Medium Duty, Compact, IEC, Type XCKP & XCKT
Discount Schedule	T
GTIN	00785901468318
Package Quantity	1
Weight	0.73 lbs.
Availability Code	Stock Item: This item is normally stocked in our distribution facility.
Returnability	Y
Country of Origin	ID

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

Generated: 01/11/2013 19:09:58