

Cabtite
CABTITE KEL SNAP B4

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Cabtite enables you to feed pre-assembled lines through the electrical cabinet wall while maintaining IP54-level protection. As the cable does not have to be split, the manufacturer's guarantee is not invalidated.

General ordering data

Type	CABTITE KEL SNAP B4
Order No.	1048190000
Version	Snap-on frame, Mounting frame, for cable entry strips, Cabtite, Polyamide, Black, -20 °C - 80 °C
GTIN (EAN)	4032248785001
Qty.	10 pc(s).

Data sheet

Cabtite CABTITE KEL SNAP B4

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Net weight	44.5 g
------------	--------

General information

Material	Polyamide	Operating temperature range, max.	80 °C
Operating temperature range, min.	-20 °C	UL 94 flammability rating	V-0

Classifications

ETIM 3.0	EC002287	ETIM 4.0	EC002287
ETIM 5.0	EC002287	ETIM 6.0	EC002624
eClass 6.2	27-14-92-01	eClass 7.1	27-14-92-01
eClass 8.1	27-14-92-01	eClass 9.0	27-14-44-38
eClass 9.1	27-18-92-65		

Approvals

ROHS	Conform
------	---------

Downloads

Brochure/Catalogue	CAT 5 ENCL 17/18 EN
Engineering Data	EPLAN, WSCAD