

**Clamping yoke
KLBUE 3-8 SC**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Product image**Shielding and earthing**

Our protective earth conductor and shielding terminals featuring different connection technologies allow you to effectively protect both people and equipment from interference, such as electrical or magnetic fields. A comprehensive range of accessories rounds off our range.

General ordering data

| | |
|------------|-------------------------------------|
| Type | KLBUE 3-8 SC |
| Order No. | 1692261001 |
| Version | Clamping yoke, Clamping yoke, Steel |
| GTIN (EAN) | 4032248032365 |
| Qty. | 10 pc(s). |

**Clamping yoke
KLBUE 3-8 SC**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Dimensions and weights

| | | | |
|----------------------------|---------|-----------------|------------|
| Width | 14.5 mm | Width (inches) | 0.571 inch |
| Height | 18.5 mm | Height (inches) | 0.728 inch |
| Depth | 26 mm | Depth (inches) | 1.024 inch |
| Mounting dimension - width | 13.5 mm | Net weight | 10.794 g |

Temperatures

| | | | |
|---------------------------|---------------|---------------------------|-------|
| Storage temperature, max. | 40 °C | Storage temperature, min. | 10 °C |
| Storage temperature | 10 °C...40 °C | | |

Material data

| | | | |
|----------|-------|--------|--------|
| Material | Steel | Colour | silver |
|----------|-------|--------|--------|

System specifications

| | |
|---------|-------------------------|
| Version | For a shield connection |
|---------|-------------------------|

Additional technical data

| | | | |
|--------------------------|---------|---------------------|-----------------|
| Explosion-tested version | No | Installation advice | Direct mounting |
| Type of fixing | Snap-on | Type of mounting | Screw |

Conductors for clamping (rated connection)

| | | | |
|----------------------|------|----------------------|------|
| Cable diameter, max. | 8 mm | Cable diameter, min. | 3 mm |
|----------------------|------|----------------------|------|

Dimensions

| | | | |
|------------------|---------|-----------------|-------|
| Length of thread | 5.65 mm | Pitch in mm (P) | 14 mm |
|------------------|---------|-----------------|-------|

Classifications

| | | | |
|-------------|-------------|------------|-------------|
| ETIM 6.0 | EC002020 | ETIM 7.0 | EC002020 |
| eClass 9.0 | 27-14-11-50 | eClass 9.1 | 27-14-11-50 |
| eClass 10.0 | 27-14-11-50 | UNSPSC | 30-21-18-01 |

Approvals

Approvals



ROHS Conform

Downloads

| | |
|--------------------|--|
| Brochure/Catalogue | CAT 1 TERM 16/17 EN |
| Engineering Data | EPLAN, WSCAD |
| Engineering Data | STEP |
| User Documentation | Beipackzettel_KLBUE.pdf StorageConditionsTerminalBlocks |