

Cable glands
VG M25-EXI BL

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Cable glands that may be used for ATEX applications

General ordering data

Order No.	1737370000
Type	VG M25-EXI BL
Version	Cable glands, Cable gland, Polyamide, External thread: M 25 x 1.5, Miscellaneous: Not specified
GTIN (EAN)	4008190956844
Qty.	20 pc(s).

**Cable glands
VG M25-EXI BL**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Length	42 mm	Net weight	15.8 g
--------	-------	------------	--------

Approvals

Approval for cable gland	Ex i II, II 2 GD
--------------------------	------------------

General information

AF size 1	32 mm	Cable gland	metric
Clamp insert	Polyamide	Clamping range, bolted connection , max.	19 mm
Clamping range, min. test adapter	13 mm	Colour code	RAL 5012
External thread	M 25 x 1.5	Length of thread	13 mm
Material	Polyamide	Operating temperature range, max.	80 °C
Operating temperature range, min.	-20 °C	Pitch of thread	1.5 mm
Protection degree with GWDR	IP 68	Seal insert	TPE
Torque for cap nut, max.	6.5 Nm	Torque for cap nut, min.	6.5 Nm
Torque for connecting adapter, max.	6.5 Nm	Torque for connecting adapter, min.	6.5 Nm
UL 94 flammability rating	V-2		

Classifications

ETIM 2.0	EC000441	ETIM 3.0	EC000441
UNSPSC	30-21-18-01	eClass 4.1	27-14-12-11
eClass 5.1	27-14-91-11	eClass 6.0	27-14-91-11
eClass 7.0	27-14-91-11		

Approvals

Approvals

