

Accessories
TS 35X15/2.3 2M/AL/BK**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com**Product image**

Similar to illustration

General ordering data

Type	TS 35X15/2.3 2M/AL/BK
Order No.	1848290000
Version	Rail, TS 35, TS 35 x 15, without slot, Aluminium, untreated
GTIN (EAN)	4032248385614
Qty.	2 m

Creation date August 18, 2020 2:57:45 AM CEST

Catalogue status 14.08.2020 / We reserve the right to make technical changes.

Data sheet

Accessories TS 35X15/2.3 2M/AL/BK

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Width	35 mm	Width (inches)	1.378 inch
Height	35 mm	Height (inches)	1.378 inch
Depth	15 mm	Depth (inches)	0.591 inch
Net weight	330 g		

Mounting rail

Permitted thermal current for PEN function, max.	232 A	Short circuit strength corresponds to E-Cu wire	95 mm ²
Short-time withstand current according to IEC 60947-7-2	11.4 kA/1s	Thickness	2.3 mm

Classifications

ETIM 6.0	EC001285	ETIM 7.0	EC001285
eClass 9.0	27-40-06-02	eClass 9.1	27-40-06-02
eClass 10.0	27-40-06-02	UNSPSC	30-21-18-01

Approvals

ROHS	Conform
------	---------

Downloads

Brochure/Catalogue	CAT 1 TERM 16/17 EN
Engineering Data	EPLAN, WSCAD, Zuken E3.S
Engineering Data	STEP
User Documentation	StorageConditionsTerminalBlocks