

**Industrial Ethernet
IE-XM-RJ45/IDC-B**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Mounting rail outlet, RJ45 module design according to IEC 60603-7-51, for wires with diameters up to 1.6 mm

General ordering data

Delivery status	This article will no longer be available in the future.
Available until	2015-04-01
Type	IE-XM-RJ45/IDC-B
Order No.	8891980000
Version	Terminal rail outlet, RJ45 module EIA/TIA 568 B, IP 20, Cat.6 (ISO/IEC 11801)
GTIN (EAN)	4032248636938
Qty.	1 pc(s).
Alternative product	8808360000

Data sheet

Industrial Ethernet IE-XM-RJ45/IDC-B

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Net weight 55.4 g

Temperatures

Operating temperature, max.	70 °C	Operating temperature	-25 °C...70 °C
Storage temperature		Installation temperature	

Downloads

GL Approval Guidelines	GL_Certificate.pdf	GOST Approval	POCC DE.ME25.B01411.pdf
------------------------	--------------------	---------------	----------------------------

General data

Category	Cat.6 (ISO/IEC 11801)	Colour	Light Grey
Configuration	Inspection window for labelling 1 TE pitch dimension acc. to DIN 43880. insta-compatible	Connection 1	
Connection 2	IDC	Description of article	RJ45 RJ45 module EIA/TIA 568 B
Housing main material	PA 66, UL 94: V-0	Plugging cycles	750
Protection degree	IP 20	Type of mounting	TS 35
Wire connection diameter, flexible, max.	0.48 mm	Wire connection diameter, flexible, min.	0.48 mm
Wire connection diameter, solid, max.	0.64 mm	Wire connection diameter, solid, min.	0.4 mm
Wire cross-section, finely stranded, max. (AWG)	AWG 26	Wire cross-section, finely stranded, min. (AWG)	AWG 26
Wire cross-section, solid, max. (AWG)	AWG 22	Wire cross-section, solid, min. (AWG)	AWG 24
Wiring	In compliance with EIA/TIA 586-B		

Electrical properties

Contact resistance	≤ 20 mΩ	Current-carrying capacity at 50 °C	1 A
Dielectric strength, contact / contact	≥ 1000 V DC	Dielectric strength, contact / shield	≥ 1500 V DC
Insulation resistance	500 MΩ	PoE / PoE+	conforming to IEEE 802.3at

Standards

Connector standard	IEC 60603-7-5	Certificate No. (GERMLLOYD)	3345 1-06
Certificate no. (cULus)	E316369		

Classifications

ETIM 3.0	EC001264	ETIM 4.0	EC001264
ETIM 5.0	EC001264	ETIM 6.0	EC001264
UNSPSC	43-17-27-10	eClass 5.1	27-25-05-04
eClass 6.2	27-25-05-04	eClass 7.1	27-25-05-04
eClass 8.1	19-17-01-25	eClass 9.0	19-17-01-25

Data sheet

**Industrial Ethernet
IE-XM-RJ45/IDC-B**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Approvals

Approvals



ROHS

Conform

Data sheet

**Industrial Ethernet
IE-XM-RJ45/IDC-B**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

Dimensioned drawing

