

## VSPC VSPC BASE 1CL FG R

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



Base element for the pluggable VSPC arresters. Integrated PE foot in the base of the impedance-neutral VSPC BASE and **floating earth PE connection (FG)** via integrated **sparkover gap**, safely discharges up to 20 kA (8/20  $\mu$ s) and 2.5 kA (10/350  $\mu$ s) to PE. Suitable for unearthened signal circuits.

### General ordering data

|            |  |
|------------|--|
| Type       | VSPC BASE 1CL FG R   |
| Order No.  | <a href="#">8951740000</a>   |
| Version    | Surge protection, Flange-mounted housing, 450 mA, IEC 61643-21, IEC 62305, DIN EN 60079-0:2009, DIN EN 60079-11:2007, DIN EN 60079-26:2007, DIN EN 61241-11:2006 |
| GTIN (EAN) | 4032248742981  |
| Qty.       | 1 pc(s).   |

Creation date April 27, 2020 3:55:51 PM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

**VSPC**  
**VSPC BASE 1CL FG R**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**
**Dimensions and weights**

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Width      | 17.8 mm | Width (inches)  | 0.701 inch |
| Height     | 98 mm   | Height (inches) | 3.858 inch |
| Depth      | 69 mm   | Depth (inches)  | 2.717 inch |
| Net weight | 70 g    |                 |            |

**Temperatures**

|                             |                |                             |                |
|-----------------------------|----------------|-----------------------------|----------------|
| Humidity                    | 5...96 %       | Operating temperature, max. | 70 °C          |
| Operating temperature, min. | -40 °C         | Storage temperature, max.   | 80 °C          |
| Storage temperature, min.   | -40 °C         | Operating temperature       | -40 °C...70 °C |
| Storage temperature         | -40 °C...80 °C |                             |                |

**Environmental Product Compliance**

|            |                |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

**Rated data UL**

|                      |         |                |                     |
|----------------------|---------|----------------|---------------------|
| Certificate No. (UL) | E311081 | UL certificate | UL 497b Certificate |
|----------------------|---------|----------------|---------------------|

**Connection data, remote alert**

|  |                     |  |                     |
|--|---------------------|--|---------------------|
| Connection type                                    | Screw connection    | Max. torque  | 0.2 Nm              |
| Stripping length                                   | 6 mm                | Cross-section for connected wire, solid core, min. | 0.5 mm <sup>2</sup> |
| Cross-section for connected wire, solid core, max. | 1.5 mm <sup>2</sup> |  |                     |

**CSA protection data**

|  |      |                                    |        |
|--|------|------------------------------------|--------|
| Gas group C                              | IIB  | Gas group D                        | IIA    |
| Gas groups A, B                          | IIC  | Input current, max. I <sub>I</sub> | 450 mA |
| Internal inductance, max. L <sub>I</sub> | 0 µH |                                    |        |

**General data**

|                           |                    |                   |                                    |
|---------------------------|--------------------|-------------------|------------------------------------|
| Colour                    | black              | Design            | Terminal, miscellaneous            |
| Optical function display  | No                 | Protection degree | IP20                               |
| Rail                      | TS 35, TS 35 x 7.5 | Segment           | Measurement - Monitoring - Setting |
| UL 94 flammability rating | V-0                | Version           | Flange-mounted housing             |

**Insulation coordination acc. to EN 50178**

|                    |   |                        |     |
|--------------------|---|------------------------|-----|
| Pollution severity | 2 | Surge voltage category | III |
|--------------------|---|------------------------|-----|

**VSPC**  
**VSPC BASE 1CL FG R**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data****Rated data IEC / EN**

|                          |           |                                      |  |
|--------------------------|-----------|--------------------------------------|--|
| Voltage type             |           | Standards                            | IEC 61643-21, IEC 62305, DIN EN 60079-0:2009, DIN EN 60079-11:2007, DIN EN 60079-26:2007, DIN EN 61241-11:2006 |
|                          | AC/DC     |                                      |  |
| Leakage current at $U_n$ | 0 $\mu$ A | Dielectric strength at FG against PE | $\geq$ 500 V   |
| Rated current $I_N$      | 450 mA    | Signalling contact                   | $U_N$ 250 V AC 0.1 A 1CO at VSPC R with VSPC control unit  |

**Further details of approvals**

|                  |                 |
|------------------|-----------------|
| GOST certificate | GOST-Zertifikat |
|------------------|-----------------|

**Connection data**

|  |                     |  |                     |
|--|---------------------|--|---------------------|
| Type of connection   | Screw connection    | Stripping length, rated connection                         | 7 mm                |
| Tightening torque, min.                                    | 0.5 Nm              | Tightening torque, max.                                    | 0.8 Nm              |
| Clamping range, min.                                       | 0.5 mm <sup>2</sup> | Clamping range, max.                                       | 4 mm <sup>2</sup>   |
| Wire cross-section, solid, min.                            | 0.5 mm <sup>2</sup> | Wire cross-section, solid, max.                            | 4 mm <sup>2</sup>   |
| Wire connection cross section, finely stranded, max.       | 2.5 mm <sup>2</sup> | Conductor cross-section, flexible, AEH (DIN 46228-1), min. | 0.5 mm <sup>2</sup> |
| Conductor cross-section, flexible, AEH (DIN 46228-1), max. | 2.5 mm <sup>2</sup> | Connection cross-section, stranded, min.                   | 0.5 mm <sup>2</sup> |
| Connection cross-section, stranded, max.                   | 2.5 mm <sup>2</sup> | Blade size   | 0.6 x 3.5 mm        |

**Classifications**

|             |             |            |             |
|-------------|-------------|------------|-------------|
| ETIM 6.0    | EC000472    | ETIM 7.0   | EC000472    |
| eClass 9.0  | 27-13-08-03 | eClass 9.1 | 27-13-08-07 |
| eClass 10.0 | 27-13-08-03 | UNSPSC     | 30-21-19-21 |

**Approvals**

Approvals



ROHS Conform

**Downloads**


|   |   |
|---|---|
| Approval/Certificate/Document of Conformity | <a href="#">CE PAPER</a>                |
| Brochure/Catalogue                          | <a href="#">CAT 4.4 ELECTR 16/17 EN</a> |
| Engineering Data                            | <a href="#">EPLAN, WSCAD</a>            |
| Engineering Data                            | <a href="#">STEP</a>                    |
| User Documentation                          | <a href="#">Instruction sheet</a>       |

**VSPC  
VSPC BASE 1CL FG R**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Drawings**

**Electric symbol**



Circuit diagram

| Cate-<br>gory | Testing<br>pulse         | Surge<br>voltage                | Surge<br>current                 | Pulse | Type   |
|---------------|--------------------------|---------------------------------|----------------------------------|-------|--|
| C1            | Quick-<br>rising<br>edge | 0.5 - 2 kV<br>with<br>1.2/50 µs | 0.25 - 1 kA<br>mit<br>8/20 µs    | 300   | Surge<br>voltage<br>arrester                               |
| C2            | Quick-<br>rising<br>edge | 2 - 10 kV<br>with<br>1.2/50 µs  | 1 - 5 kA<br>mit<br>8/20 µs       | 10    | Surge<br>voltage<br>arrester                               |
| C3            | Quick-<br>rising<br>edge | ≥ 1 kV<br>with<br>1 kV/µs       | 10 - 100 A<br>mit<br>10/10000 µs | 300   | Surge<br>voltage<br>arrester                               |
| D1            | High<br>power            | ≥ 1 kV                          | 0.5 - 2.5 kA<br>mit 10/350<br>µs | 2     | Arrester for<br>lightning<br>current and<br>surge voltages |

Discharge capacity