

WK S 0,6X3,5

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

**Interchangeable bits for torque screwdriver**

Drive output acc. to DIN 5264, ISO 2380/1

General ordering data

Type	WK S 0,6X3,5
Order No.	9918540000
Version	Screwdriver insert, Blade width (B): 3.5 mm, 175 mm, Blade thickness (A): 0.6 mm
GTIN (EAN)	4032248388905
Qty.	1 pc(s).

WK S 0,6X3,5**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

Technical data**Dimensions and weights**

Width	175 mm	Width (inches)	6.89 inch
Height	4 mm	Height (inches)	0.157 inch
Depth	4 mm	Depth (inches)	0.157 inch
Weight	26 g	Net weight	22 g

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

Screwing tools

Blade length	175 mm	Blade thickness (A)	0.6 mm
Blade width (B)	3.5 mm	Form	Slotted

Classifications

ETIM 6.0	EC002116	ETIM 7.0	EC002116
eClass 9.1	21-04-04-90	eClass 10.0	21-04-04-90
UNSPSC	27-11-28-14		

Approvals

Approvals

**Downloads**

Brochure/Catalogue [CAT 3 HDC 17/18 EN](#)
[CAT 6 TOOLS 15/16 EN](#)
[CAT 5 ENCL 17/18 EN](#)